



G3 Premium System Process Chart

For All Paint Systems (including the very latest energy or 'hyper' clearcoats)

Remove Defect

Wet Sanding

- G Sand Denibbing **GSD320**
Rose P2000
- G Sand Denibbing Block **GSA301**
- G Sand Waterproof Half Sheets
- P1500 **GSW115**
- P2000 **GSW120**
- G Sand Flattening Block **GSA012**

Dry Sanding

- G Sand 75mm Abrasive Film Discs
- P1200 **GSD712**
- P1500 **GSD715**
- P2000 **GSD720**
- P3000 (foam discs) **GS3701**
- G Sand 150mm Abrasive Film Discs
- P1200 **GSD112**
- P1500 **GSD115**
- P2000 **GSD120**
- P3000 (foam discs) **GS3101**
- G Sand 150mm Interface Pad **GSA106**
- G Sand Universal Back Up Pad (150mm) **GSA101**

Stage 1: CUT

G3 Premium Abrasive Compound

1 Stage 1: CUT

Product Size
500g
1kg

Codes
G3P506
G3P101

Applicators

- G Mop 3" Yellow Compounding Foam **GMC312**
- G Mop 6" Yellow Compounding Foam **GMC612**
- G Mop 8" Yellow Compounding Foam **GMC812**

Stage 2: FINISH (if needed)

G3 Premium Abrasive Compound

2 Stage 2: FINISH

Product Size
500g
1kg

Codes
G3P506
G3P101

Applicators

- G Mop 3" Finishing Foam **GMF301**
- G Mop 6" Finishing Foam **GMF601**
- G Mop 8" Finishing Foam **GMF801**

Stage 1: CUT

Attach a G Mop Back Plate and a G Mop Yellow Compounding Foam to a polisher

Shake bottle well before use

Dispense a small quantity of product onto surface or pad

Stage 2: FINISH (if needed)

NO NEED FOR A SECOND COMPOUND

If swirl marks or holograms remain use the same process as in Stage 1: **CUT** but with a G Mop Finishing Foam and a small (pea-sized) quantity of G3 Premium.

Applicator Back Plates

- G Mop Back Plate with Yellow Interface for 6" Pads
GMB614 (14mm thread size)
GMB658 (5/8" thread size)
GMB616 (16mm thread size)
- G Mop Flexible Back Plate for 8" Pads
GMB814 (14mm thread size)
GMB858 (5/8" thread size)
GMB816 (16mm thread size)

Compound at 1500 - 1800rpm

Wipe clean with a Finishing Cloth **FC-3** (3 x cloths)

Tip: Prior to first use of a new pad, roughen with a Spurring Brush (**1090005**) to ensure optimum results. Clean pad with the Spurring Brush after use.

Stage 3: PROTECT

G3 Glaze Gloss Enhancer

3 Stage 3: PROTECT

G3 Wax Premium Liquid Protection

Product Size	Codes	Product Size	Codes
500ml	G3G501	500ml	G3W501
1 ltr	G3G101	1 ltr	G3W106
1 US gallon	G3G118	1 US gallon	G3W118

Applicators for both products

- G Mop 3" Finishing Foam **GMF301**
- G Mop 6" Finishing Foam **GMF601**
- G Mop 8" Finishing Foam **GMF801**
- Finishing Cloth (3 x cloths) **FC-3**

Stage 3: PROTECT - G3 Glaze (for fresh paint)

Attach a G Mop Back Plate and a G Mop Finishing Foam to a polisher

Shake bottle well and apply a small quantity to the pad

Compound at 1000 - 1500rpm

Wipe clean with a Finishing Cloth **FC-3** (3 x cloths)

Stage 3: PROTECT - G3 Wax (for fully cured paint)

Shake bottle well and apply a small quantity to the surface or cloth

Rub the product in a circular motion onto the surface

Allow to dry to a haze

Wipe clean with a Finishing Cloth **FC-3** (3 x cloths)

