

Profile Finish

Liquid Compound







Product Description

Profile Finish is a very fine finishing compound designed to remove any light swirl marks and holograms from high quality painted lacquered and gel coat surfaces to leave the ultimate high gloss finish. It will not scratch and is particularly good on soft coatings which are susceptible to swirl marks.

Profile Finish is ideally applied using a Farécla G Mop Finishing Foam, which was engineered in tandem with the compound to provide optimum performance. For a higher cut, use with a G Mop Lambs Wool Pad.



Product Information

Size	Code	Ctn Qty
1 ltr	PRF101	6
1 US gallon	PRF106	2

Key Benefits

• Value	Economical in use due to its low viscosity
Swirl & Hologram Remover	Swirls and holograms are quickly eliminated permanently
Surface Restorer	Restores dull surfaces and enhances colour
Gentle Action	Fine abrasive formulation removes marks without scratching
Dry Use & Clean to Use	Easy clean up, minimal splatter or dusting
• High Gloss Result	Gives a high shine finish with good depth and clarity



Use With

Primary Applicator



G Mop Finishing Foam **GMF301** (3" / 75mm) **GMF601** (6" / 150mm) **GMF801** (8" / 200mm)



G Mop Flexible Back Plate for 8" Pads GMB814 (14mm thread) **GMB858** (5/8" thread) GMB816 (16mm thread)



Yellow interface for 6" Pads GMB614 (14mm thread) **GMB658** (5/8" thread)

GMB616 (16mm thread)

G Mop Back Plate with



Farécla Finishing Cloth FC-3 (3 x cloths)

Secondary Applicator (for a higher cut)



G Mop Lambs Wool Pad **GML301** (3" / 75mm) **GML601** (6" / 150mm) **GML801** (8" / 200mm)



G Mop Flexible Back Plate for 8" Pads GMB814 (14mm thread) **GMB858** (5/8" thread) GMB816 (16mm thread)



Yellow interface for 6" Pads GMB614 (14mm thread) **GMB658** (5/8" thread) GMB616 (16mm thread)

G Mop Back Plate with



Farécla Finishing Cloth FC-3 (3 x cloths)

How To Use











Technical Information

Appearance: White coloured liquid

Viscosity: Low viscosity VOC Content: 190g/L Relative Density: 1.05

pH: 7 - 8

Paint Type Compliance: All paint types

Additional Information

Clean applicators before and after use with a Spurring Brush to prevent dried product damaging the surface being worked on.



Spurring Brush 1090005