

<b>IDENTIFICATION</b>			
8.1 Product Name:	ARTMIL BALSA WOOD GLUE		
8.2 Other Names:	Premium Craft Glue		
8.3 Manufacturer's Product Code:	1030		
UN Number:	1133		
Dangerous Goods Class:	3		
Packaging Group:	11		
Subsidiary Risk:	not applicable		
8.6 Hazchem Code:	3[Y]E		
8.8 Poisons Schedule No.:	S5		
8.10 Use:	Craft Glue is a mixture of synthetic resins dissolved in solvent, it is designed for use as a general purpose craft adhesive, e.g in the making of craftwork, millinery applications and making of lampshades etc.		
Linked barcodes:	<b>Barcode</b>		<b>Description</b>
	9312393030061		Artmil Balsa Wood Glue 50ml
Other:			
<b>Physical Description</b>		<b>Other Properties</b>	
8.16 Appearance:	Clear colourless liquid.	8.23a Shock Sensitivity:	not available
8.17 Boiling Point/Melting Point:	IBP: > 50 degrees Celsius	8.23b Corrosiveness:	not corrosive
8.18 Vapour Pressure:	not available	8.23c Oxidising Properties:	not available
8.19 Specific Gravity:	approximately 0.91	8.23d Reactivity with Common Substances:	not available
8.20 Flash	Lowest solvent FP < - 10	8.23e Auto-	not available

Point:	degrees Celsius (closed cup)	Ignition Temperature:	
8.21 Flammability Limits:	not available	8.23f Evaporation Rate:	not available
8.23 Solubility in Water:	insoluble	8.23g Vapour Density:	not available
Other:		8.23h Odour Threshold:	Strong Ketonic odour
		8.23i pH:	
		8.23j Solubility in Organic Solvents:	
		8.23k Per Cent Volatiles:	
		8.23l Volatile Organic Compounds:	
		8.23m Bulk Density:	
		Other:	
<b>Ingredients</b>	8.27 Chemical Name	8.28 CAS No.	8.29 Proportion
	Hydrocarbon solvent	not applicable	0 - < 50%
	acetone	67-64-1	50 - 100 %
<b>9 HEALTH HAZARD INFORMATION</b>		<b>10 PRECAUTIONS FOR USE</b>	
<b>9.2 Health Effects</b>		10.4 Exposure Standards:	No National Occupational Health and Safety Commission (NOHSC) exposure standards are assigned for this product. However exposure standards for constituents are listed on this MSDS. As with all chemicals, exposure should be maintained to the least possible levels. Acetone: TWA 500ppm

			(1190mg/m <sup>3</sup> ); STEL 1000ppm (2380mg/m <sup>3</sup> )
Acute		10.10 Engineering Controls:	Use in a well ventilated area only. Open container cautiously as contents may be under pressure. Build up of mists or vapours in the atmosphere must be prevented. Avoid inhalation of vapours. Do not store or use in confined spaces. Prevent concentration in hollows and sumps. Do not enter these areas until atmosphere has been checked.
Swallowed:	Ingestion may result in gastrointestinal irritation, in particular nausea, abdominal pain, vomiting and diarrhoea. Ingestion may also lead to aspiration of material into the lungs and central nervous system (CNS) depression. CNS effects include dizziness, drowsiness, confusion, headache, muscular weakness and loss of consciousness. Prolonged exposure to a large quantity can ultimately lead to coma and possibly death.	10.13 Personal Protection:	Approved respirators may be necessary to prevent overexposure by inhalation. Depending on the working environment, Impervious gloves recommended, to prevent eye contact wear safety glasses, chemical goggles or face shield as appropriate. Expert advice should be sought. Subsequent to handling product, do not eat or drink until after washing hands thoroughly.
Eye:	Eye contact and solvent vapour may cause moderate eye irritation. Symptoms may include redness, pain, stinging, tearing or swelling or blurred vision.	10.18 Flammability:	This product is a class 3 Flammable Liquid in accordance with the Australian Dangerous Goods Code 6th Edition.
Skin:	Skin contact or solvent vapour may cause irritation including, itching, redness or rash. Prolonged and repeated exposure may cause skin dryness or cracking resulting	Other:	

	in dermatitis.		
Inhaled:	Inhalation may lead to irritation of the respiratory system. Symptoms of overexposure may include fatigue, headache, drowsiness, dizziness, shortness of breath and possible nausea. Very high concentrations of product vapour may cause central nervous system depression which can lead to loss of coordination, impaired judgement, and, if exposure is prolonged, unconsciousness or death.	<b>11 SAFE HANDLING INFORMATION</b>	
<b>Chronic</b>	Prolonged and repeated exposure through inhalation, ingestion or skin contact will result in harmful effects including central nervous system depression. Systemic effects of chronic exposure can also include damage to kidneys and liver especially where exposure is repeated and prolonged with no personal protection. Excessive skin exposure may also result in irritation leading to dermatitis.	11.1 Storage and Transport:	Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store in well ventilated area. Keep containers securely sealed and protected against physical damage. Classified as a dangerous good for transport class 3. Class 3 Flammable liquids shall not be loaded in the same vehicle with: - Class 1: Explosives, - Class 2.1: Flammable gases (when both in bulk), -Class 2.3: Poisonous gases, -Class 4.2: Spontaneously combustible substances, - Class 5.1: Oxidising agents, -Cl
<b>9.30 First Aid</b>		11.4 Spills and Disposal:	Shut off all possible sources of ignition - no smoking. Wear appropriate protective clothing. Contain all spills with inert, non combustible, absorbent material. DO

			NOT use combustible materials such as sawdust. Using non sparking tools and equipment; collect the material and place into a suitable labelled and sealed container. Confirm to all local, state and federal regulations and guidelines for waste disposal. Do not flush or allow spillage to enter into drains or sewers.
Swallowed:	DO NOT induce vomiting. Seek immediate medical attention. contact Poison Information Service Aust 13 1126 New Zealand 0800 764 766	11.11 Fire/Explosion Hazard:	Product is highly flammable. Isolate from source of heat, naked flame, sparks and strong oxidising materials. Take precaution against static electricity discharges. Earth and bond all process equipment including tanks & drums. Ensure adequate ventilation to prevent an explosive vapour air mixture. Vapours will travel considerable distances to sources of ignition and flash back.
Eye:	Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical attention.	Other:	Suitable extinguishing media: Use foam, dry chemical or carbon dioxide extinguishers. Do NOT use water jet.
Skin:	Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If irritation, swelling, redness or blistering occurs seek medical advice.		
Inhaled:	Remove the source of contamination or move victim to fresh air immediately. If not breathing, apply artificial respiration at once and seek		

	urgent medical advice. If irritation develops and persists, seek medical attention		
<b>First Aid Facilities</b>	Ensure that safety shower and eye wash are available.		
<b>9.33 Advice to Doctor</b>	Treat symptomatically. Extreme caution must be taken to prevent aspiration.		
<b>Other</b>			
<b>GENERAL</b>			
<b>General</b>	ARTMIL BALSAMIC WOOD GLUE		
<b>SUPPLIER</b>			
<b>Supplier</b>	CSA Trading Pty Ltd		
<b>Supplier Date</b>	April 2012		
<b>13 CONTACT POINT:</b>			
13.1 Contact Title:			
13.1 Contact 'Phone:	Poison Info centre (Australia 13 11 26) New Zealand 0800 764 766		
13.1 Contact Pager:			

MSDS Supplied by: CSA Trading Pty Ltd on date: April 2012