



# Cloud 9 Radiance

## Cloud 9 Crumb

Suitable for Heavy Contract Use

For Use in Doublestick and Stretch-Fit Applications

Designed for use with under-floor heating

**CLOUD**



**RANGE OF UNDERLAYS**

*Radiance*

Top Surface	Spun Bonded Polypropylene	
Bottom Surface	Corona Treated Polymer Film	
Nominal Thickness	5.00 mm	
Nominal Roll Weight	15.2 Kg	33.5 lb
Weight Per Unit Area	1009 g/m <sup>2</sup>	30 oz/yd <sup>2</sup>
Roll Length	11.0 m	36.0 ft
Roll Width	1.37 m	54 in
Guarantee	Lifetime of the Carpet (When used in recommended areas)	

## Recommended Areas of Use

Suitable for heavy contract use large areas and installations where a flat firm fitting is required

BS. 5808 : 1991 Test Results - British Standard for Carpet Underlays

End Use Classification	BS. 5808	HC/U
Work of Compression after 1000 impacts	BS. 4098	>90 J/m <sup>2</sup>
Retention of Work of Compression	BS. 4098	>90 %
Loss in Thickness after Static Loading	BS. 4939	<5.00 %
Loss in Thickness after Dynamic Loading	BS. 4052	<5.00 %
Resistance to Cracking	BS. 5808 (A)	Pass

### Disclaimer

Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Ball and Young has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.

