

Medical Refrigeration

Bromic MediFridge™

SAFE TEMPERATURE CONTROL



A number of Bromic's MediFridge™ are listed on the
- QCPP Compliant
Dispensary Refrigerator list
Listed models - MED0140GD, MED0374GD



Bromic MediFridge™ allows for safe Temperature Control on all shelves for storage of vaccines, vitamins, and other sensitive products.

Bromic's long history in Refrigeration brings expertise and unmatched service backed by our unrivaled 2 year warranty providing peace of mind. A number of Bromic MediFridge™ models are on the QCPP Compliant Dispensary Refrigerator list.



Product Features



+ Alarm (Audible & visual)

Ensures items are not accidentally overexposed to warm temperatures

+ Integrated Digital Thermostat

For temperature accuracy and consistency

+ Factory installed lock

Ensures additional security

+ LED lighting

To optimise visibility for stored content and energy efficiency

+ Adjustable PVC coated shelves

For easy positioning and cleaning

+ Airflow Shelving

To ensure cool air is evenly distributed throughout the cabinet (improved airflow)

+ Fan-forced cooling system

Ensures the temperature remains consistent throughout unit

+ Self-closing door

To ensure constant temperature retention

+ Min/Max temperature recording

| Model | MED0140GD | MED0220GD | MED0374GD |
|---------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Part Number | 3736213 | 3736217 | 3736218 |
| Ext. Height (mm)* | 820 | 1310 | 1840 |
| Ext. Width (mm)* | 595 | 595 | 595 |
| Ext. Depth (mm)* | 595 | 598 | 598 |
| Capacity | 145L | 215L | 372L |
| Temp. Range | +2°C - 8 °C | +2°C - 8 °C | +2°C - 8 °C |
| Plug Supplied | ✓ | ✓ | ✓ |
| Power Supply | 10A | 10A | 10A |
| Features | | | |
| Internal Light | ✓ | ✓ | ✓ |
| Door Shape | Flat with Straight Corners | Flat with Straight Corners | Flat with Straight Corners |
| Feet Included | 30mm Feet at Front. Rollers at back | 30mm Feet at Front. Rollers at back | 30mm Feet at Front. Rollers at back |
| No. of Shelves Incl. Base | 4 | 4 | 4 |
| Default Door Hinge | Right | Right | Right |
| Warranty | | | |
| Parts | 2 | 2 | 2 |
| Labour | 2 | 2 | 2 |



Multi-Use USB Temperature Recorder

A cost effective and reliable solution which records data without special hardware or software

Track temperature variations for real-time information about your products

Connect the LogTag® to your device with its integrated, long-life USB connector

Analyse all recorded data in an automatically generated PDF or Excel report.

Product Highlights

- Automatically generates a report
View data in a PDF report, excel file or an encrypted LogTag data file
- Fully user configurable
Individual alarm settings, start options, trip length and log interval
- Simply connects to your computer via USB
- Records up to 16,129 readings
Provides over 3 months logging at 10 minute sample intervals



Specifications: LogTag® Data Logger

| PART NUMBER | 350700050 |
|----------------------|--|
| Measurement Range | -22° C - +70° C |
| Capacity | 16,129 Real time temperature recording, non-volatile memory |
| Sampling Interval | 2° C - 8 °C |
| Start Options | Push button start or specific date/time |
| Start up delay | Configurable from 1 minute to 72 hours |
| Environmental | IEC 60529: IP64 with USB cap fitted |
| Power Source | 3V Lithium battery - non replaceable |
| Battery Life | 2-3 years of normal use, based on 15 minute logging and monthly data download |
| Size | 93mm(H) x 54.5mm (w) x 8.6mm (T) including USB cap |
| Weight | 35g |
| Case Material | Polycarbonate |
| Alarm Functions | High/low, single, consecutive and cumulative alarm events, 'OK'/'ALERT' indicators |
| Connection Interface | USB 2.0, High durability, metal A-type plug |
| Software | Adobe Reader, LogTag Analyzer® 2.6 or higher |

Accuracy/Resolution Charts

