VS12TC PORTABLE REFRIGERATOR

Vacc-Safe

Vacc-Safe portable refrigerators are suitable for transporting products between 2 -6°C. This 12L unit is suitable for use on an aircraft due to not having a compressor.









Security

Audible and Visual Alarms. Safety Lock.

Built-In Backup Battery

Built in battery to display temperature when power is off.

Single LED Display

High accuracy single LED displays.

| Item | Model No. | VS12TC |
|--------------------|---|---------------------|
| Technical data | Cabinet Type | Portable |
| | Cooling Type | Semiconductive |
| | Weight (kg) | 6 |
| | Refrigerant | N/A |
| | Total Storage Volume(L) | 12L |
| | External Material | ABS |
| | Inner Material | Aluminium plate |
| Control | Controller | Microprocessor |
| | Display | LED |
| | Temperature Accuracy(°C) | 0.1 |
| | Temperature Range | 2 to 6°C |
| Dimensions | Product Dimensions(mm | 520*300*270 |
| | (wxdxh) Interior Dimensions(mm) (wxdxh) | 430*150*180 |
| | Packing Dimensions(mm) (wxdxh) | 520*300*270 |
| Electrical data | Power Supply Rated Power(W) | 240V AC / 12-24V DC |
| | High Temperature | 95W |
| Functions | Alarm Low Temperature | Υ |
| | Alarm Power | Y |
| | Failure Alarm | Υ |
| | Caster | N |
| | Holding Time 25°C Empty | >1 |
| | Holding Time 25°C Loaded | >2 |

Temperature Retention.

Up to 2 Hour Temperature hold without power (32°C ambient temperature load situation)



Input voltage.

240 Volt and 12 Volt. Dual-use car and home, car 12/24V DC or household 100-240V AC with power adapter for work.



