

Upright Display Fridge 1126L - 2 Door - Flat Glass

| Upright Display Fridge



Food safe storage
with 3M1 climate class

5 adjustable shelves plus
base for display flexibility

Energy-efficient R290
natural refrigerant

Self-closing doors ensure
tight seal every time to
minimise heat transfer

High-impact LED
lights on all sides of
the door and inside
the unit for maximum
product exposure

Argon filled Low-E double
glazed glass for improved
condensation performance

Fully compliant
with Australian safety
standards and regulations

2 Years Bromic Extra Care
Warranty - Labour and Parts


43°C maximum ambient
temperature for consistent
cooling even in extreme heat

Lockable front castors for
easy and secure positioning

Accurate
temperature control
with digital controller

Upright Display Fridge 1126L - 2 Door - Flat Glass

| Upright Display Fridge



SPECIFICATIONS				DIMENSIONS	
Part Number	3736236	Internal Light	LED	External (mm)	
Volume	1126L	Colour Temp.	6500K	Width	1200
Unit Weight	195kg	No. of Doors	2	Depth	775
Packaged Weight	210kg	Door Type	Glass	Height	2095
Adjustable Temp. Range	-1 to 5°C	Door Glass Type	Double glazed Low-E Glass + Argon Gas	Internal (mm)	
Max. Ambient Temp. Range	43°C	Door Shape	Flat	Width	1090
Climate Class	3M1	Door Style	Hinged	Depth	674
GEMS Star Rating	5	Door Lock	Yes	Height	1500
Energy Consumption	8.64kWh/24h	Self-Closing Door	Yes	Packaged (mm)	
Refrigeration Capacity	1097W	Door Swing Dimension	512mm	Width	1240
Refrigerant	R290	Total Depth of Door Open	1303mm	Depth	790
Air-Circulation	Fan Forced	No. of Shelves incl. Base per door	6	Height	2120
Rated Current	5A	Shelf Type	Adjustable		
Electrical Voltage	220-240V	Shelf Dimensions	1072(w) x 527(d) mm		
Frequency	50Hz	Temp. Controller	Digital		
Power Supply	Single Phase	Castors	Yes		
Power Plug	1 x 10A	Colour	Silver		
Plug Location	Rear, bottom right	Warranty	2 Years Bromic Extra Care Warranty - Labour and Parts		
Cord Length	1m				