

NLMDR LABORATORY REFRIGERATOR

DUAL REFRIGERATION

NULINE
REFRIGERATION

The Nuline NLMDR Dual Refrigeration System Laboratory Refrigerator is a bespoke solution that is built in Australia with 2 independent refrigeration systems.

In the rare circumstance of a refrigeration system failure the second refrigeration system exists to provide the required refrigeration to prevent loss of stock.

A solution for high value refrigerated storage requirements and where failure is not acceptable.

FEATURES

- Top Mounted System dual refrigeration systems
- E-Glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Interior Lighting LED
- Automatic Water Disposal
- Digital Display with Built-in Alarms



2°C to 8°C



1136 L
1839 L
2377 L



1200w x 750d x 2100h
1880w x 750d x 2100h
2400w x 750d x 2100h



CONTACT US:



1300 885 693



info@ozcoolers.com.au



www.ozcoolers.com.au



NLMDR LABORATORY REFRIGERATOR

DUAL REFRIGERATION



Model	NLMDR1000/2	NLMDR1614/3	NLMDR2170/4
Gross Capacity	1136 L	1839 L	2377 L
External Dimensions in mm (w/d/h including castors)	1200 x 750 x 2100	1880 x 750 x 2100	2400 x 750 x 2100
Internal Dimensions in mm (w/d/h)	1100 x 600 x 1520	1780 x 600 x 1520	2300 x 600 x 1520
Packed Dimensions in mm (w/d/h including pallet)	1300 x 850 x 2250	1980 x 850 x 2250	2500 x 850 x 2250
Gross Weight - kg (packed weight)	167	217	238
Net Weight - kg	155	205	225
Voltage	240V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R134a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	White Colourbond		
Inner Liner Material	White Colourbond		
Door	Solid / Glass E-Glass		
Door Hinge	LH / RH	LH / RH / RH	LH / RH / LH / RH
Door Handle	Lockable		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Optional		
Door Ajar Alarms	Optional		
High and Low Readout	Visual / Audible		
Remote Alarm Contacts			
(BMS Connectivity for Alarms only)	Optional		
(BMS Connectivity for Temperatures)	Optional		
Port Entry	Optional		
Battery Back-up for Controller	Optional		
Power Requirement	10amp GPO		
Castors	Yes		
Adjustable Shelves	5	15	20
Usable Shelf Area in mm(w/d)	1080 x 580	565 x 580	575 x 580
Light	LED		

We recommend that the refrigeration system is switched from one to the other on a regular basis (for example, weekly). This provides operational readiness for the organisation.

Nuline Refrigeration reserves the right to alter the specifications without prior notice.