




NLMS SPARK SAFE LABORATORY REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- E-glass and heated cabinet facia to prevent condensation up to 80% R.H.
- Glass or Solid Door
- Auto Water Disposal
- Hot Gas Defrost
- Castors
- Door Lock
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- TGA Certified



	2°C to 8°C
	400 L 700 L 1000 L 1614 L
	600w x 620d x 1915h 870w x 700d x 2100h 1200w x 700d x 2100h 1880w x 700d x 2100h

CONTACT US:

 **1300 885 693**
 **info@ozcoolers.com.au**
 **www.ozcoolers.com.au**



NLMS SPARK SAFE LABORATORY REFRIGERATOR



Model	NLMS400/1	NLMS700/1	NLMS1000/2	NLMS1614/3
Gross Capacity	400 L	700 L	1000 L	1614 L
External Dimensions in mm (w/d/h including castors)	600 x 620 x 1915	870 x 700 x 2100	1200 x 700 x 2100	1880 x 700 x 2100
Internal Dimensions in mm (w/d/h)	500 x 470 x 1435	770 x 550 x 1555	1100 x 550 x 1555	1780 x 550 x 1520
Packed Dimensions in mm (w/d/h including pallet)	700 x 720 x 2065	970 x 800 x 2250	1300 x 800 x 2250	1980 x 800 x 2250
Gross Weight - kg (packed weight)	102	112	137	187
Net Weight - kg	95	95	125	175
Voltage	240V			
Temperature Range	2°C to 8°C			
Ambient Temperature Range	10°C to 32°C			
Refrigerant	R134a			
Cooling System / Defrost	Static			
Exterior Cabinet Finish	White Colourbond			
Inner Liner Material	White Colourbond			
Door	Solid / Glass E-Glass			
Door Hinge	RH		LH / RH	LH / RH / RH
Door Handle	Lockable			
Type of Controller	Digital			
Temperature Display	External			
Data Logger	Optional			
Door Ajar Alarms	Optional			
High and Low Readout	Visual / Audible			
BMS Connectivity (BMS Connectivity for Remote Alarms only)	Optional			
(BMS Connectivity for 4-20mA Transmitter)	Optional			
Port Entry	Optional			
Battery Back-up for Controller	N/A			
Power Requirement	10amp GPO			
Castors	Yes			
Adjustable Shelves		5		15
Usable Shelf Area in mm(w/d)	480 x 450	750 x 530	1080 x 530	565 x 530
Light	LED			

Nuline Refrigeration reserves the right to alter the specifications without prior notice.