

MFi REFRIGERATOR INCUBATOR




NULINE
REFRIGERATION

Select from our new series of Refrigerated Incubators. Our MFi 70 is a premium stainless steel refrigerator equipped with a Microprocessor Controller with timing function, that offers a total control over the temperature of your items. The features of this model make it unique and suitable to satisfy your high standard needs.

FEATURES

- Top Mounted System
- Cabinet Finish in Stainless Steel Interior/Exterior
- Automatic Defrost and Water Disposal
- 5 Adjustable Shelves per Door
- Available in Glass Door (TNG) or Solid Door (TN)
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 40°C
	700 L 1400 L
	740w x 830d x 2050h 1480w x 830d x 2050h

CONTACT US:

 **1300 885 693**
 **info@ozcoolers.com.au**
 **www.ozcoolers.com.au**



MFi REFRIGERATOR INCUBATOR



Model	MFi70TN/G	MFi140TN/G
Gross Capacity	700 L	1400 L
External Dimensions in mm (w/d/h including castors)	740 x 830 x 2050	1480 x 830 x 2050
Internal Dimensions in mm (w/d/h)	600 x 690 x 1475	1340 x 690 x 1475
Packed Dimensions in mm (w/d/h including pallet)	760 x 850 x 2100	1500 x 850 x 2100
Gross Weight - kg (packed weight)	134	225
Net Weight - kg	120	201
Voltage	240V	
Temperature Range	2°C to 40°C	
Ambient Temperature Range	10°C to 32°C	
Temperature Fluctuation	±1.5°C	
Refrigerant	R290	
Cooling System / Defrost	Fan Forced / Automatic	
Exterior Cabinet Finish	Stainless Steel	
Inner Liner Material	Stainless Steel	
Door	Solid / Glass	
Door Hinge	RH	LH / RH
Door Handle	Pull Handle	
Type of Controller	Digital / Microprocessor	
Temperature Display	External	
Data Logger	Optional	
Door Ajar Alarms	Optional	
High and Low Readout	Visual / Audible	
BMS Connectivity		
(BMS Connectivity for Remote Alarms only)	Optional	
(BMS Connectivity for 4-20mA Transmitter)	Optional	
Port Entry	Optional	
Battery Back-up for Controller	Optional	
Power Requirement	10amp GPO	
Castors	Yes	
Adjustable Shelves	5	10
Usable Shelf Area in mm(w/d)	530 x 652	
Light	LED	



Nuline Refrigeration reserves the right to alter the specifications without prior notice.