specifications



PG400HFr-2

Solid Swing Doors

Electronic

Controller

SKOPE Gen2 Pegasus Horizontal 1/1 REMOTE 3 Door Freezer (JH5303)

1649

1421

CABINET DIMENSIONSExternalInternalHeight:716mm*570mmWidth:1649mm1301mmDepth:680mm545mmFloor area:1.12m²

* Height excludes castors, legs or optional worktop.


Dimensional tolerances Before installing this cabinet allow the following dimensional tolerances:	
Linear dimensions	Overall cabinet dimensions
Less than 1 metre	±5mm
More than 1 metre	-5mm to +10mm

 Length of multiple cabinets

 At each joint
 At each end wall

 ±5mm
 +15mm

 -5mm to +10mm
 +15mm



Evaporator box and service compartment

28

æ.

Copyright © 2008 SKOPE Industries Limited

-0

CABINET SPECIFICATIONS	
Refrigeration system:	Electronic controlled, side mounted, remote refrigeration unit
Refrigerant:	Thermostatic expansion valve fitted to suit R134a/R404A/R452A
Pipe connection size:	Liquid line: 1/4". Suction line: 3/8"
Remote refrigeration duty:	550 Watts
Cabinet internal volume:	410 litres
Insulation:	60mm thick, high density cyclo-isopentane polyurethane foam
Cabinet temperature range:	-18°C to -21°C up to 43°C ambient
Drainage:	Evaporator drain fitted inside service compartment (requires plumbing)
Electrical:	230-240 Volts a.c. 50 Hz, 4.61 Amps
Internal lighting:	2 x 5W T8 LED tubes (Ø26 x 360mm) - Door activated
Internal door opening size:	3 door openings: 570mm high x 365mm wide
Doors:	Solid stainless steel, self-closing doors (with key lock) - LH & RH hinged
Worktop (optional):	Optional 35mm stainless steel worktop with 65mm square edged fascia
Shelves:	Two levels of non-tip, adjustable tray slides and/or shelves per door
Weight:	130 kg

427

716

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0188 Rev 2.2 Nov. 2019



SKOPE INDUSTRIES LIMITED

New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533 Email: enquiry@skope.co.nz Website: www.skope.co.nz