


Adjustable Windshield System

Yamaha Star Venture 2018

Please read this entire manual before proceeding with installation.



Installation of this MadStad system is very simple. You will not need to modify the bike.

STEP 1: Remove the factory shield

Unscrew the factory windshield screws and remove the windshield. Save the screws.


STEP 2: Attach the MadStad base shield and brackets

Our base windshield attaches where the factory shield just came out, and our brackets attach right on top. Use the factory screws to attach these items onto your bike. The brackets will be oriented as shown on Page 1 with the black adjustment knobs up and facing inward.

STEP 3:

Windshield Installation

- 1. Pre-install the Truss screws & washers into the windshield holes as shown in the image below.
- 2. Once all four of the screws are in place, gently guide the screws into the Well Nuts in the brackets until all four are set.
- 3. Hand tighten the Truss screws until they swell up behind the bracket and are firmly holding the windshield.



Adjusting the MadStad Brackets

The knob screws release the brackets allowing the windshield to slide and tilt. One turn loosens the shield for height adjustment only, and 3-4 turns allows you to change the angle. These knob screws must always be tightened securely before riding and DO NOT attempt to adjust the brackets while riding! You must come to a complete stop before adjusting.



Start with the angle at about the middle of the bracket range, and the top of the shield at about your chin level as you look straight ahead. Then tighten the brackets and go for a ride. Experiment with different positions at different speeds until you find a combination of height and rake angle that eliminates buffeting and gives a smoother ride.

Disclaimer

Neither MadStad Engineering nor its owners shall be liable for any damages, consequential or inconsequential, resulting from the use of our products. Installation of any of our products constitutes acceptance of these terms. It is the responsibility of the user to make sure all fasteners are tightened securely, the windshield is mounted properly and the adjustment knobs are tightened snugly before putting the motorcycle in motion. MadStad systems ARE NOT intended to be adjusted while the vehicle is in motion; you must pull over out of the way of traffic and come to a complete stop before making any changes. The user must never place the windshield in such a position as to interfere with the safe and complete movement of the handlebars and controls.

Returns and Warranty

MadStad adjustable brackets carry a lifetime warranty against manufacturing defects. This does not include cosmetic issues nor any parts that inherently wear out or degrade over time such as rubber and plastic parts. Windshields, deflectors, and other similar plastic parts are warrantied for 1 year against manufacturing defects, not against cosmetic issues or issues related to normal wear and tear. Please visit our website for further details.

MadStad Engineering, Inc.

1451 E. Jefferson St., Brooksville, FL 34601 U.S.A.

Phone: 352-848-3646 Fax: 352-240-3911

Web Site: http://www.madstad.com

Email: support@madstad.com

Thank you for your support, and ride safely!

