

# SPROCKET

## NO.60

### Finished Bore

### 3/4" PITCH

#### TYPE F- BORED TO SIZE

No. Teeth	Catalog No	Outside Dia. Do	LTB L	Weight Lbs. (App.)	Stock Finished Bores Includes Keyway and Setscrew
9	60B9F	2.510	1 1/4	.6	3/4 -7/8 -1
10	60B10F	2.760	1 1/4	.7	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4
11	60B11F	3.000	1 1/4	.9	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4
12	60B12F	3.250	1 1/4	1.3	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4 -17/16
13	60B13F	3.490	1 1/4	1.3	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2
14	60B14F	3.740	1 1/4	1.6	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2
15	60B15F	3.980	1 1/4	1.7	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4
16	60B16F	4.220	1 1/4	2.1	3/4 -7/8 -1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4
17	60B17F	4.460	1 1/4	2.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
18	60B18F	4.700	1 1/4	2.6	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
19	60B19F	4.950	1 1/4	3.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
20	60B20F	5.190	1 1/4	3.9	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
21	60B21F	5.430	1 1/4	4.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
22	60B22F	5.670	1 1/4	4.7	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
23	60B23F	5.910	1 1/4	5.0	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
24	60B24F	6.150	1 1/4	5.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
25	60B25F	6.390	1 1/4	5.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
26	60B26F	6.630	1 1/4	5.8	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
27	60B27F	6.870	1 1/4	6.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
28	60B28F	7.110	1 1/4	6.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
29	60B29F	7.350	1 1/4	6.9	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
30	60B30F	7.590	1 1/4	7.1	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
31	60B31F	7.830	1 1/4	7.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
32	60B32F	8.070	1 1/4	7.8	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
33	60B33F	8.300	1 1/4	8.2	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
34	60B34F	8.540	1 1/4	8.5	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
35	60B35F	8.780	1 1/4	8.8	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16
36	60B36F	9.020	1 1/4	9.2	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
37	60B37F	9.260	1 1/4	9.9	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
38	60B38F	9.500	1 1/4	10.5	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
39	60B39F	9.740	1 1/4	10.9	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
40	60B40F	9.980	1 1/4	11.2	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
41	60B41F	10.220	1 1/4	11.8	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
42	60B42F	10.460	1 1/4	12.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
43	60B43F	10.700	1 1/4	13.0	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
44	60B44F	10.940	1 1/4	13.5	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
45	60B45F	11.180	1 1/4	13.8	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
46	60B46F	11.420	1 1/4	14.1	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
47	60B47F	11.650	1 1/4	14.6	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
48	60B48F	11.890	1 1/4	15.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
49	60B49F	12.130	1 1/4	16.4	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
50	60B50F	12.370	1 1/4	17.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
51	60B51F	12.610	1 1/4	18.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
52	60B52F	12.850	1 1/4	19.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
53	60B53F	13.090	1 1/4	20.3	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
54	60B54F	13.330	1 3/4	21.0	1 -1 1/8 -13/16 -1 1/4 -13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
55	60B55F	13.570	1 3/4	21.2	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
56	60B56F	13.810	1 3/4	21.3	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
57	60B57F	14.040	1 3/4	22.2	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
58	60B58F	14.280	1 3/4	23.0	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
59	60B59F	14.520	1 3/4	23.8	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
60	60B60F	14.760	1 3/4	25.0	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
70	60B70F	17.150	1 3/4	31.4	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
72	60B72F	17.630	2	33.5	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
80	60B80F	19.540	2	41.2	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
84	60B84F	20.490	2	45.8	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
96	60B96F	23.360	2 1/4	62.3	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16
112	60B112F	27.180	2 1/4	81.0	-13/8 -17/16 -1 1/2 -15/8 -13/4 -115/16 -2 -23/16 -27/16

Hub diameters vary to suit different Bore Sizes.  
KEYWAY IS ON CENTER LINE OF TOOTH.