



DEEP GROOVE BALL BEARINGS - TWO SEALS WITH SNAP RING

	d	D	B	L	M	(lbs.)	NICE	FED / Schatz
7508 DLG	.5000	1.7500	.6250	.7500	-	.310	7508 DLG	W508
7510 DLG	.6250	1.7500	.6250	.7500	-	.310	7510 DLG	W510
7512 DLG	.7500	1.7500	.6250	.7500	-	.250	7512 DLG	W512
7514 DLG	.8750	2.0000	.6250	.7500	-	.360	7514 DLG	W514
7516 DLG	1.0000	2.0000	.6250	.7500	-	.340	7516 DLG	W516
7518 DLG	1.1250	2.5625	.7500	.8750	-	.710	7518 DLG	W518
7520 DLG	1.2500	2.5625	.7500	.8750	-	.670	7520 DLG	W520

TWO SEALS SNAP RING - EXTENDED INNER RACE

7608 DLG	.5000	1.7500	.6250	1.0920	10-32	.400	7608 DLG	WE508
7610 DLG	.6250	1.7500	.6250	1.0920	10-32	.360	7610 DLG	WE510
7612 DLG	.7500	1.7500	.6250	1.0920	10-32	.310	7612 DLG	WE512
7614 DLG	.8750	2.0000	.6250	1.1790	10-32	.450	7614 DLG	WE514
7615 DLG	.9380	2.0000	.6250	1.1790	10-32	.440	7615 DLG	WE515
7616 DLG	1.0000	2.0000	.6250	1.1790	10-32	.380	7616 DLG	WE516
7617 DLG	1.0625	2.5625	.7500	1.4170	1/4-28	1.120	7617 DLG	WE517
7618 DLG	1.1250	2.5625	.7500	1.4170	1/4-28	1.010	7618 DLG	WE518
7620 DLG	1.2500	2.5625	.7500	1.4170	1/4-28	.950	7620 DLG	WE520

NOTE:

- 1.) This series is manufactured from 52100 steel and hardened to Rockwell hardness 60/64 C scale.
- 2.) This series is equipped with ribbon type steel retainer.
- 3.) 7600 DLG series has two set screws 120° apart in the inner race.
- 4.) These two series are equipped with land riding seals and dust shrouds.