

**REPAIR**

All repair work shall be performed by the manufacturer. All other repair work or modification may void the warranty and releases CMC Rescue, Inc. from all liability and responsibility as the manufacturer.

**SAMPLE INSPECTION AND MAINTENANCE LOG**

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____		Date in Service _____	
Brand/Model _____		Strength _____	
Date	How Used or Maintained	Comments	Name

**CMC Rescue, Inc.**  
 6740 Cortona Drive, Goleta CA 93117  
 USA  
 805-562-9120 / 800-235-5741  
 cmcrescue.com

**ISO 9001:2008 Certified**

©2015 CMC Rescue, Inc. Control No. 201106.01.062713

**USER INFORMATION**

CMC Rescue recommends separating the User Information from the Pick Off Strap and retaining the information in a permanent record. CMC also recommends making a copy of the information to keep with the strap and that the information should be referred to before and after each use.

**INSPECTION**

Inspect the equipment according to your department's policy for inspecting life safety equipment. The equipment should be inspected after each use by an inspector that meets your department's training standard for inspection of life-safety equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should do a cursory inspection before each use.

The service life of equipment used for rescue depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

When inspecting the equipment, check the webbing for cuts, worn or frayed areas, broken fibers, soft or hard spots, or discoloration. Check the stitching for pulled threads, abrasion, or broken stitches. If any damage is noted, the equipment should be removed from service.

If the equipment is dropped or impact loaded, it should be inspected by a qualified inspector prior to being returned to service. In most cases, a visual inspection will not be able to determine if the equipment has been damaged. Based on the history of the incident, if there is any doubt regarding the safety of the equipment, it should be removed from service and destroyed.

**IMPORTANT INFORMATION - PLEASE READ AND SAVE**



**Pick Off Strap**

**Made in USA**  
of US and foreign components



**WARNING**

- **SERIOUS INJURY OR DEATH MAY RESULT FROM THE IMPROPER USE OF THIS EQUIPMENT.**
- **THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.**
- **DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PROPER TRAINING.**
- **USE, INSPECT, AND REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**

**USE**

1.) Using a locking carabiner, connect the V-ring Adjuster into your lowering system. Secure the D-ring in a location that will not be in the way of the descent, such as on your harness gear loop.

2.) When you reach the subject, connect the D-ring into his harness with a locking carabiner. Position yourself and adjust the length of the strap (using the V-ring Adjuster) so the subject is where you want him to be, and the Pick Off Strap is under tension. This reduces the risk of shock loading the system when you add the subject's weight.

Although we have found that the strap works best in this configuration, the D-ring may be attached to the lowering system and the V-ring attached to the subject's harness.

When used in conjunction with the CMC Lifesaver Victim Harness (Part No. 202405):

1.) Connect the D-ring to the Victim Harness tie-in point with a locking carabiner prior to your descent.

2.) Secure the Victim Harness to the subject and remove the slack by adjusting the length of the Pick Off Strap.

For easy carry and handling, the Pick Off Strap and Lifesaver Victim Harness may be kept in the storage bag. The CMC Pick Off Strap works best in a lowering based pick off, but may also be used in rappel pick off. Contact the CMC Rescue School at (800) 235-5741 for more information.

**MAINTENANCE**

If the strap becomes soiled, it can be washed in cold water with a mild detergent. CMC recommends the use of LifeLine Cleaner. Dry out of direct sunlight. Do not dry in an automatic dryer. Constructed of steel and nylon materials.