

USER INFORMATION

User Information shall be provided to the user of the product. NFPA Standard 1983 recommends separating the User Information from the equipment and retaining the information in a permanent record. The standard also recommends making a copy of the User Information to keep with the equipment and that the information should be referred to before and after each use.

Additional information regarding auxiliary equipment can be found in NFPA 1500, *Standard on Fire Department Occupational Safety and Health Programs* and NFPA 1983, *Standard on Life Safety Rope and Equipment for Emergency Services*.

INSPECTION

Inspect the equipment according to your department's policy for inspecting life safety equipment. The equipment should be inspected after each use by an inspector that meets your department's training standard for inspection of life-safety equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should do a cursory inspection before each use.

The service life of equipment used for rescue depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

Inspect the sideplates for cracks or dents. The swivel eye should turn freely without resistance. While the sheave on most pulleys will not "spin" it should still turn freely. Check the axle assembly for tightness.

If any significant damage is observed, the equipment should be removed from service. Minor nicks or sharp spots may be smoothed with emery paper.

If the equipment is dropped or impact loaded, it should be inspected by a qualified inspector prior to being returned to service. In most cases, a visual inspection will not be able to determine if the equipment has been damaged. Based on the history of the incident, if there is any doubt regarding the safety of the equipment, it should be removed from service and retired.

USING THE AZTEK PULLEYS

The AZTEK Omni Pulleys are designed to be used in pairs in a pre-rigged mechanical advantage system using 8mm cord. The end of the cord can be secured around the "horn" of one of the pulleys and secured with the supplied end cap. A Prusik hitch can be used for progress capture and can be secured directly to the pulley via the plunger pin. Both the horn and the plunger pin have a minimum breaking strength of 12 kN. The AZTEK Omni pulleys can be rigged in either a 5:1 or a 4:1 mechanical advantage configuration. At any given time only one Prusik hitch is used. When not in use the Prusik cord should be loosened and allowed to float on the cord.

To prevent roll-out, use only locking carabiners.

MAINTENANCE

Clean and dry this equipment after each use to remove any dust, debris, and moisture. During use, carrying, and storage keep the equipment away from acids, alkalis, and strong chemicals. Do not expose the equipment to flame or high temperatures. Store in a cool, dry location. Do not store where the equipment may be exposed to moist air, particularly where dissimilar metals are stored together.

REPAIR

All repair work shall be performed by the manufacturer. All other work or modifications may void the warranty and releases CMC Rescue, Inc. from all liability and responsibility as the manufacturer.

SAMPLE LOG

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____		Date in Service _____	
Brand/Model _____		Strength _____	
Date	How Used or Maintained	Comments	Name

IMPORTANT INFORMATION - PLEASE READ AND SAVE



AZTEK Omni Pulley

Made in USA
of US and foreign components



Product Label

WARNING

- **FAILURE TO FOLLOW THESE INSTRUCTIONS OR IMPROPER USE OF THIS EQUIPMENT COULD RESULT IN SERIOUS INJURY OR DEATH.**
- **THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.**
- **DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PROPER TRAINING.**
- **USE, INSPECT, AND REPAIR ONLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.**



THIS PULLEY MEETS THE AUXILIARY EQUIPMENT REQUIREMENTS OF NFPA 1983, STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES, 2012 EDITION.

EMERGENCY SERVICES AUXILIARY EQUIPMENT
IN ACCORDANCE WITH NFPA 1983 - 2012.

- **RATED FOR TECHNICAL USE (T)**
- **MBS 47 kN (10,565 lbf)**

CMC Rescue, Inc.
6740 Cortona Drive, Goleta, CA 93117
USA
805-562-9120 / 800-235-5741
cmcrescue.com

ISO 9001:2008 Certified