

IMPORTANT INFORMATION - PLEASE READ AND SAVE



CMC Pulleys

Made in USA
of US and foreign components

Product Label

30030X Rescue Pulleys
3005XX ProTech Pulleys
30043X Swivel Pulleys

! WARNING

- **FAILURE TO FOLLOW THESE INSTRUCTIONS OR IMPROPER USE OF THIS EQUIPMENT COULD RESULT IN SERIOUS INJURY OR DEATH.**
- **THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.**
- **DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PROPER TRAINING.**
- **USE, INSPECT, AND REPAIR ONLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.**



THIS PULLEY MEETS THE AUXILIARY EQUIPMENT REQUIREMENTS OF NFPA 1983, STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES, 2012 EDITION.

EMERGENCY SERVICES AUXILIARY EQUIPMENT
IN ACCORDANCE WITH NFPA 1983-2012.

- **300301 RESCUE PULLEY, GENERAL USE (G) MBS 55 kN (12,364 lbf)**
- **300302 RESCUE DOUBLE PULLEY, GENERAL USE (G) MBS 50 kN (11,240 lbf)**
- **300501 PROTECH SINGLE PULLEY, GENERAL USE (G) MBS 43 kN (9,667 lbf)**
- **300502 PROTECH DOUBLE PULLEY, GENERAL USE (G) MBS 44 kN (9,892 lbf)**
- **300430 PMP SWIVEL PULLEY, GENERAL USE (G) MBS 45 kN (10,116 lbf)**
- **300432 SWIVEL DOUBLE PULLEY, GENERAL USE (G) MBS 44 kN (9,892 lbf)**
- **300434 1.1" SWIVEL PULLEY, TECHNICAL USE (T) MBS 22 kN (4,945 lbf)**
- **300436 2.6" SWIVEL PULLEY, GENERAL USE (G) MBS 50 kN (11,240 lbf)**

CMC Rescue, Inc.
6740 Cortona Drive, Goleta CA 93117
USA
805-562-9120 / 800-235-5741
cmcrestue.com

ISO 9001 Certified

©2016 CMC Rescue, Inc. Control No. 300XXX.092316

USER INFORMATION

User Information shall be provided to the user of the product. NFPA Standard 1983 recommends separating the User Information from the equipment and retaining the information in a permanent record. The standard also recommends making a copy of the User Information to keep with the equipment and that the information should be referred to before and after each use.

Additional information regarding auxiliary equipment can be found in NFPA 1500, *Standard on Fire Department Occupational Safety and Health Programs*, and NFPA 1983, *Standard on Life Safety Rope and Equipment for Emergency Services*.

- **To prevent roll-out, use only locking carabiners.**
- **When using swivel pulleys, make sure that the sideplates are locked prior to use.**
- **When using a Prusik hitch in conjunction with a pulley, care must be taken to prevent the Prusik knot from being pulled in between the side plates of the pulley.**

INSPECTION

Inspect the equipment according to your department's policy for inspecting life safety equipment. The equipment should be thoroughly inspected after each use by an inspector that meets your department's training standard for inspection of life safety equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should inspect the equipment before each use.

Inspect the equipment for cracks, sharp edges, dents, corrosion, burrs or excessive wear. Inspect for elongation of the carabiner hole. Where applicable, the sideplates should rotate easily but not feel loose. While the sheave on most pulleys will not "spin" it should still turn freely. Check the axle assembly for tightness. Minor nicks or sharp spots may be smoothed with emery cloth. If any of the above is noted, or if the equipment has been subjected to shock loads, fall loads, or abuse other than normal use, remove the equipment from service and destroy it. If there is any doubt about the serviceability of the equipment, remove the equipment from service and destroy it.

The service life of equipment used for rescue depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

CARRYING, MAINTENANCE & STORAGE

Clean and dry this equipment after each use to remove any dust, debris and moisture. During use, carrying and storage keep the equipment away from acids, alkalis, rust and strong chemicals. Do not expose the equipment to flame or high temperatures. Store in a cool, dry location. Do not store where the equipment may be exposed to moist air, particularly where dissimilar metals are stored together.

REPAIR

All repair work shall be performed by the manufacturer. All other work or modifications will void the warranty and releases CMC Rescue, Inc. from all liability and responsibility as the manufacturer.

SAMPLE LOG

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____		Date in Service _____	
Brand/Model _____		Strength _____	
Date	How Used or Maintained	Comments	Name