



PMP SWIVEL PULLEY 1.1



PMP SWIVEL PULLEY



SWIVEL DOUBLE PULLEY



PMP SWIVEL PULLEY 2.6

SWIVEL PULLEYS

Great for building M/A Systems!

Our Swivel Pulleys are ideal for building Mechanical Advantage systems, high anchor points or tripod use, and for backcountry and industrial applications. The rotating swivel aligns the rope with the direction of the pull. By combining the swivel with the pulley, the overall system length is minimized, increasing travel. The patented pivoting side plate allows the rope to be quickly inserted without having to disconnect from the carabiner. Our swivel pulleys are milled from a solid block of aircraft-grade aluminum for strength optimization and weight reduction.

Note: The stainless steel sheave on the PMP Swivel Pulley part #300430 can be used with either life safety rope or wire cable applications.



UL Classified to NFPA 1983 (2012 ED)



- Side plate opens without having to disconnect the pulley from the carabiner or anchor
- Double-detent button prevents accidental opening of side plate
- Sealed ball bearings provide maximum efficiency
- Certified with rope sizes up to 13mm
- UL Classified to NFPA 1983 (2012 ED)

ITEM #	DESCRIPTION	WEIGHT	SHEAVE	SHEAVE TREAD SIZE	3 SIGMA MBS	NFPA RATING
300434	PMP SWIVEL PULLEY 1.1	5.1 OZ (145 G)	ALUMINUM	1.1 x 0.5 IN (28 x 13 MM)	22 kN (4,946 LBF)	TECHNICAL USE
300430	PMP SWIVEL PULLEY	11.3 OZ (320 G)	STAINLESS STEEL	1.5 x 0.5 IN (38 X 13 MM)	45 kN (10,116 LBF)	GENERAL USE
300432	SWIVEL DOUBLE PULLEY	14.6 OZ (414 G)	ALUMINUM	1.5 x 0.5 IN (38 X 13 MM)	44 kN (9,891 LBF)	GENERAL USE
300436	PMP SWIVEL PULLEY 2.6	1 LB 14 OZ (850 G)	ALUMINUM	2.6 x 0.5 IN (66 x 13 MM)	50 kN (11,240 LBF)	GENERAL USE

INFORMATION

CMC Rescue, Inc.

800 235 5741 | 805 562 9120

email | info@cmcrecue.com

cmcrecue.com