

USER INFORMATION

User Information shall be provided to the user of the product. NFPA Standard 1983 recommends separating the User Information from the equipment and retaining the information in a permanent record. The standard also recommends making a copy of the User Information to keep with the equipment and that the information should be referred to before and after each use.

Additional information regarding auxiliary equipment can be found in NFPA 1500, *Standard on Fire Department Occupational Safety and Health Programs*, and NFPA 1983, *Standard on Life Safety Rope and Equipment for Emergency Services*.

INSPECTION

Inspect the equipment according to your department's policy for inspecting life safety equipment. The equipment should be inspected after each use by an inspector that meets your department's training standard for inspection of life-safety equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should do a cursory inspection before each use.

The service life of equipment used for rescue depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

Inspect the equipment for cracks, dents, or elongation of the carabiner holes. If any significant damage is observed, the equipment should be removed from service. Minor nicks or sharp spots may be smoothed with emery paper.

If the equipment is dropped or impact loaded, it should be inspected by a qualified inspector prior to being returned to service. In most cases, a visual inspection will not be able to determine if the equipment has been damaged. Based on the history of the incident, if there is any doubt regarding the safety of the equipment, it should be removed from service and retired.

USING THE ANCHOR PLATE

The design of the Anchor Plate is such that the large hole provides a focal point for connectors linking to a proper anchorage. The smaller holes provide connection points for auxiliary system equipment such as system lowering and belay devices.

MAINTENANCE

Clean and dry this equipment after each use to remove any dust, debris, and moisture. During use, carrying, and storage keep the equipment away from acids, alkalis, and strong chemicals. Do not expose the equipment to flame or high temperatures. Store in a cool, dry location. Do not store where the equipment may be exposed to moist air, particularly where dissimilar metals are stored together.

REPAIR

All repair work shall be performed by the manufacturer. All other work or modifications may void the warranty and releases CMC Rescue, Inc. from all liability and responsibility as the manufacturer.

SAMPLE LOG

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____		Date in Service _____	
Brand/Model _____		Strength _____	
Date	How Used or Maintained	Comments	Name

IMPORTANT INFORMATION - PLEASE READ AND SAVE



Anchor Plate Micro-Anchor Plate

Made in USA
of US and foreign components

Product Label	
300610	Aluminum Anchor Plate
300615	Stainless Steel Anchor Plate
300623	Micro Anchor Plate

⚠ WARNING

- FAILURE TO FOLLOW THESE INSTRUCTIONS OR IMPROPER USE OF THIS EQUIPMENT COULD RESULT IN SERIOUS INJURY OR DEATH.
- THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.
- DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PROPER TRAINING.
- USE, INSPECT, AND REPAIR ONLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.



THIS ANCHOR PLATE MEETS THE AUXILIARY EQUIPMENT REQUIREMENTS OF NFPA 1983, STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES, 2012 EDITION.

EMERGENCY SERVICES AUXILIARY EQUIPMENT
IN ACCORDANCE WITH NFPA 1983-2012.

- 300610 - ALUMINUM ANCHOR PLATE, GENERAL USE (G) MBS 45 kN (10,116 lbf.)
- 300615 - STAINLESS STEEL ANCHOR PLATE, GENERAL USE (G) MBS 42 kN (9,442 lbf.)
- 300623 - MICRO ANCHOR PLATE, GENERAL USE (G) MBS 46 kN (10,341 lbf.)

CMC Rescue, Inc.

6740 Cortona Drive, Goleta CA 93117

USA

805-562-9120 / 800-235-5741

cmcrestuce.com

ISO 9001:2008 Certified