

REPAIR

All repair work shall be performed by the manufacturer. All other work or modification may void the warranty and releases CMC Rescue from all liability and responsibility as the manufacturer.

SAMPLE INSPECTION AND MAINTENANCE LOG

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____		Date in Service _____	
Brand/Model _____		Strength _____	
Date	How Used or Maintained	Comments	Name

CMC Rescue, Inc.

6740 Cortona Drive, Goleta CA 93117
USA
805-562-9120 / 800-235-5741
cmcrescue.com

ISO 9001:2008 Certified

©2015 CMC Rescue, Inc. Control No. 301010.02.070913

Designed for tower climbing, the **CMC Rescue Bypass Lanyard** allows the user to maintain fall protection while climbing or traversing structures.

USER INFORMATION

CMC Rescue recommends separating the User Information from the equipment and retaining the information in a permanent record. CMC also recommends making a copy of the information to keep with the equipment and that the information should be referred to before and after each use.

INSPECTION

Inspect the equipment according to your department's policy for inspecting life-safety equipment. Equipment should be inspected after each use, and at least once a year by an inspector that meets your department's training standard for inspection of life-safety equipment. Record the date of the inspection and the results in the equipment log. Each user should be trained in equipment inspection, do a cursory inspection, and check component compatibility before each use.

When inspecting the equipment, check the webbing for cuts, worn or frayed areas, broken fibers, soft or hard spots or discoloration. Check the stitching for pulled threads, abrasion or broken stitches. If any damage is noted, the equipment should be removed from service and destroyed.

IMPORTANT INFORMATION - PLEASE READ AND SAVE



Bypass Lanyard

Made in USA
of US and foreign components

PRODUCT LABEL

⚠ WARNING

- **SERIOUS INJURY OR DEATH MAY RESULT FROM THE IMPROPER USE OF THIS EQUIPMENT.**
- **THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.**
- **DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PROPER TRAINING.**
- **USE, INSPECT, AND REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**

If the equipment is dropped or impact loaded, it should be inspected by a qualified inspector prior to being returned to service. In most cases, a visual inspection will not be able to determine if the equipment has been damaged. Based on the history of the incident, if there is any doubt regarding the safety of the equipment, it should be removed from service and destroyed.

USING YOUR BYPASS LANYARD

Connect the oval link to the waist or sternum connection point of your harness. For ascending, secure the first snap hook and follow with the second snap hook to the next step. Continue ascending while leaving one snap hook securely attached at all times. When stationary, maintain both snap hooks connected to the structure for fall protection back up.

- **Only disconnect and move one snap hook at a time.**
- **The user's center of mass should remain below the anchor point at all times.**

MAINTENANCE

If the lanyard becomes soiled, it can be washed in cold water with a mild detergent. CMC recommends the use of LifeLine Cleaner. Dry out of direct sunlight. Do not dry in an automatic dryer. Constructed of all nylon materials.