

Accelerating your research

877-3493941

Pouch Cell Heat Sealing Machine for the Sides



PC-HS is a semi automatic pouch cell heat sealing machine for sealing the sides of the cell. Usually the bottom of the cell is sealed by folding the cell cup and the two vertical sides are heat sealed. PC-HS comes with adjustable temperature settings for the top and bottom and also with timer. Each cell is manually set and sealing action is done with the foot pedal. Air compressor need to be connected with a pressure of about 0.7 Mpa. Temperature and timer settings varies depends upon the thickness of the Aluminum foils.

Part No:

Description

Operating Voltage Maximum Power

Dimensions

Air Pressure Requirement

Sealing Cell Length

Weight

Seal width

Sealing temperature

Timer Packing

Included

: PC-HS-110/PC-HS-220

: Pouch Cell Heat Sealing Machine for the sides

: 110V/220V

: 900 watts

 $: 320 \text{mm}(L) \times 320 \text{mm}(W) \times 485 \text{mm}(H)$

: 0.4 - 0.7 Mpa

: 190 mm maximum

: 32kg (70 lbs)

: 3.2 mm

: 50 - 300 C

: 0-99 Sec adjustable

: Wooden Crate

: Power cord, foot pedal,

Air tube for compressor

Feature Video: Operational Video:

Electrodes and More by Battery Consulting 4020 Christopher way Plano TX 75024 USA

