



TWO WHEEL TRACTOR IMPLEMENT CHART



BCS TWO WHEEL TRACTOR IMPLEMENTS			GROUND CULTIVATION IMPLEMENTS						
IMPLEMENT	DETAILS		PART NO.	710	728	738	740	750	770HY
Rotavator	46cm (18")		92190835	✓	✓				
	52cm (20")		92190870	✓	✓	✓ ¹			
	66cm (26")		92190871			✓	✓	✓	✓
	80cm (32")		92191243				✓	✓	✓
	85cm (34")	for 750 Petrol	921C0101					✓	
		for 750 Diesel	921C0001					✓	
	Transport Wheel (to fit all rotavators)		92242465	✓	✓	✓	✓	✓	✓
Precision Depth Roller	For 66cm Rotavator		92291312			✓	✓	✓	✓
	For 80cm Rotavator		92291311				✓	✓	✓
Power Harrow ²	60cm (24")		031.600				✓	✓	✓
	75cm (30")		039.750				✓	✓	✓
Seeder	For 75cm Power Harrow		036.750				✓	✓	✓
Stone Burier ²	62cm (24")		071.620				✓	✓	✓
Powered Rotary Plough	Single Furrow		92191306			✓	✓	✓	✓
	Reversible		ARV.D4				✓	✓	✓
Single Plough	Solid Single Furrow		92190799			✓	✓	✓	✓
Reversible Plough	Slatted Mouldboard	5" (12¾cm)	VD00		✓	✓	✓		✓
		6" (15¼cm)	VD0				✓	✓	✓
	Solid Mouldboard		92190797			✓	✓	✓	✓
Cultivator Kit	Toolbar, Frame, Reversible Plough, Adjustable Ridger & Potato Lifter	5" (12¾cm)	VD00.AE.AP.AP1066		✓	✓	✓		✓
		6" (15¼cm)	VDO.AE.AP.AP1066				✓	✓	✓
Adjustable Ridger	20-40cm (8-16")		92190798		✓	✓	✓		✓
			92149991					✓	
Trailed Ridger	Fits behind rotavator		92147860	✓	✓	✓	✓	✓	✓
3 Tined Cultivator	Adjustable Straight Tines		C3GDR		✓	✓			
5 Tined Cultivator	Adjustable Straight Tines		C5GDR			✓	✓	✓	✓
	Adjustable Spring Tines		C5GDS			✓	✓	✓	✓
5 Tined Cultivator	Self-Regulating Straight Tines		C5GMDRR			✓	✓	✓	✓
	Self-Regulating Spring Tines		C5GMDSR			✓	✓	✓	✓
7 Tined Cultivator	Adjustable Straight Tines		C7GDR			✓	✓	✓	✓
	Adjustable Spring Tines		C7GDS			✓	✓	✓	✓





TWO WHEEL TRACTOR IMPLEMENT CHART



BCS TWO WHEEL TRACTOR IMPLEMENTS			GRASS CUTTING & CLEARING IMPLEMENTS					
IMPLEMENT	DETAILS	PART NO.	710	728	738	740	750	770HY
Laser® Scythe Cutter Bar and Transmission	80cm (32")	92190978	✓	✓	✓			
	100cm (40")	92190979	✓	✓	✓			
	115cm (45")	92190980	✓	✓	✓	✓	✓	✓
	135cm (53")	92190981			✓	✓	✓	✓
	155cm (61")	92190982			✓	✓	✓	✓
	Short Oil Transmission ³	92190994			✓	✓	✓	✓
	Long Oil Transmission ³	92190995				✓	✓	✓
Duplex Scythe Cutter Bar and Transmission	130cm (51") - Laser®	92191269			✓	✓	✓	✓
	120cm (47") - Finger	92190883			✓	✓	✓	✓
	150cm (59") - Finger	92190879				✓	✓	✓
	Duplex Transmission	92190990						
Rotary Mower	56cm (22") for 4.00x8 wheels	92190783		✓	✓			
	56cm (22") for 5.00x10 and 5.00x10 wheels	92190784						
	100cm (40")	92190886				✓ ⁴	✓	✓ ⁴
Mulching Mower	80cm (32")	92190885			✓	✓	✓	✓
Flail Mower	65cm (25")	TR65			✓	✓	✓	✓
	85cm (33")	TR85				✓	✓	✓
Hay Rake	100cm (40")	MOD120/1SA	✓	✓	✓	✓	✓	✓
	120cm (47")	MOD145/1SA			✓	✓	✓	✓
Mini Baler	Bale Size 52cm x 55cm (20" x 22")	MP550				✓	✓	✓
Buck Rake	100cm (40")	BU100			✓	✓	✓	✓
Lawn Scarifier	65cm (25")	BC65			✓	✓	✓	✓





TWO WHEEL TRACTOR IMPLEMENT CHART



BCS TWO WHEEL TRACTOR IMPLEMENTS			MAINTENANCE & SNOW CLEARING IMPLEMENTS					
IMPLEMENT	DETAILS	PART NO.	710	728	738	740	750	770HY
Chipper Shredder	7cm (3")	BIO 100			✓	✓	✓	✓
Stump Grinder		FRCP				✓	✓	✓
BCS Power/Snow Brush	80cm (32")	92190890	✓	✓	✓	✓	✓	✓
	100cm (40")	92190889			✓	✓	✓	✓
	120cm (47")	92190893						
Bellon Power Brush with Optional Collector	100cm (40")	MSP 1000				✓	✓	✓
	Optional Collector	9AICAS0000				✓	✓	✓
Leaf Blower		SOFFIATORE			✓	✓	✓	✓
Dozer Blade	100cm (40")	92190735	✓	✓	✓ ⁵	✓ ⁵	✓ ⁵	✓ ⁵
Wheel Barrow	125kg capacity	WB1			✓	✓ ⁵	✓ ⁵	✓ ⁵
Snow Blower	60cm (24")	92190786	✓	✓	✓ ⁵			
	70cm (28")	92190787			✓ ⁵	✓ ⁵	✓ ⁵	✓ ⁵
Snow Plough	100cm (40")	92191234	✓	✓	✓ ⁵	✓ ⁵	✓ ⁵	✓ ⁵

NOTES:

- ¹ The 52cm (20") rotavator is narrower than the 738 wheel track.
 - ² There are three styles of roller available for the power harrow and stone burier- mesh, or solid, or cage (bars) - it is important to state which roller you require.
 - ³ The Short Oil Transmission is recommended for power units with GX160, GX200, and GX270 engines.
The Long Oil Transmission is recommended for power units with GX270, GX340, GX390, and diesel engines.
 - ⁴ When fitted to the 740, 770HY or 630 the 100cm (40") rotary mower requires an Implement Extension or Quick Release Coupling.
 - ⁵ When fitted to 738 (diesel), 740 (petrol and diesel), 750 (petrol and diesel), 770HY (petrol and diesel), 630WS, or 660HY WS, additional weights will be required to balance the implement and power unit.
- Please be aware that the BCS 750 has a different PTO to the other units in the range and is fitted with a Quick Coupling System as standard.

