

PRESSURE SWITCH OPTIONS (ALL SERIES)										
OPTION CODE	DESCRIPTION	SWITCH SERIES								NOTES
		A	B	L	P	G	F	N	H	
XBP	Wall mounting bracket (H ₂ O)		●	STD	STD	STD				
XBX	69C bushing (St. St.)									Assembled to capillary. Remote Temperature only.
XCH	Chained cover		●	●	●	●		●	●	
XCN	ATEX approval on 700 Series		●							
XC8	CSA approval	STD	●		●		STD			Standard on NEMA 4 enclosures. F series and A series.
XFM	FM approval – Single element – Dual element		● ●	● ●						N/A on temperature switches.
XFP	Fungus proofing		●	●	●	●	●	●	●	
XFS	Factory adjusted setpoint	●	●	●	●	●	●	●	●	Setpoint must be given as well as increase or decrease.
XG3	Belleville actuator		●							Setpoint limits reduced to 30% to 100% of range.
XG5	Gas/oil UL limit differential pressure control to 150" H ₂ O		●	●						Buna N & Viton diaphragm only. B400 & LDS single setpoint only. N/A w/code 22, 32, P or J switch elements.
XG6	Gas/oil UL limit pressure control to 600 psi		●	●						Buna N and Viton diaphragm only.
XG7	Special actuator with redundant seal design (SS primary diaphragm)		●							B700 switch only. UL listed.
XG8	Steam limit pressure control to 300 psi		●	●						Stainless steel or Viton diaphragm only.
XG9	Fire safe actuator		●	●	●	●				Stainless steel diaphragm only.
XHS	High static differential		●	●	●					Available with Buna N and Viton diaphragms only. 15 psid and 30 psid only.
XHX	40 psi static pressure/dp only 160 psi proof pressure/dp only 100 psi proof pressure/press only Inches of water ranges		●	●	●	●				
XJK	Left side conduit connection		●	●				●	●	Standard on 700 series. N/A with DPDT element on 400 series.
XJL	¾" to ½" conduit reducing bushing		●	●	●	●		●	●	
XK3	Terminal block		●	●	●	●	●			Terminal blocks standard with dual switches on 700 series. N/A on 400 series.
XLE	6 foot leads on the micro switch	●	●	●	●	●	●		●	
XMD	Metric range on label		●							N7 switches only. Standard on N4.
XNH	Stainless steel tagging		●	●	●	●	●	●	●	Specify tag information.
XNN	Paper tag		●	●	●	●	●	●	●	Specify tag information.
XPJ	24 Vdc pilot light(s) – Single – Dual		● ●	● ●	● ●					B, L & P Nema 4 only.
XPK	Pilot light(s), top mounted		●	●	●				●	N/A on explosion-proof enclosures.
XPM	¾" sealed conduit connection with 16" lead wires		●	●	●	●	STD		●	
XRN	Range scale		●							Standard on L, G, P & F series.
XTA	316 SS pressure port(s) for in H ₂ O ranges		●	●	●	STD				
XTM	2" pipe mounting bracket		●	●	●	●		●		

Consult factory for guidance in product selection
Phone (203) 385-0217, Fax (203) 385-0602 or
visit our web site at www.ashcroft.com

PRESSURE SWITCH OPTIONS (ALL SERIES)

OPTION CODE	DESCRIPTION	SWITCH SERIES								NOTES
		A	B	L	P	G	F	N	H	
XUD	316 stainless steel diff. press. conn.		●	●	●	STD				
X06	Pressure connection: ½ NPT male, ¼ NPT female combination		●	●	●	●	N/A	●		Standard with 1000, 2000 and 3000 psi ranges. Bottom connection only on D/P H ₂ O ranges.
X07	Pressure connection: ½ NPT female		●	●	●	●	STD			
X2C	DPDT with single setpoint adjustment			●		●				Available with LPS, LDS, LTS, GPS, GTS and GDS models.
X3A	Sanitary seal approved by 3A council	●	●	●		●				Select either 1½" or 2" Tri-Clamp seal.
X6B	Cleaned for oxygen service		●	●	●	●	●	●		N/A with Buna N diaphragm.
	Diaphragm seals	●	●	●	●	●	●	●		