

FIRST STAGE / INDUSTRIAL REGULATOR

MEGR-1630 SERIES



MEGR-1630-104/78

APPLICATION:

The MEGR-1630 Series First Stage / Industrial regulators are large capacity, high pressure units for use in conjunction with MEGR-S1202 Series regulators. They can also be used on final stage (pounds-to-pounds) service. These regulators are best suited for industrial applications where high flow capacity is required.

Part No.	Description	Inlet/Outlet	Orifice	PSIG Outlet Set Point	Outlet PSIG Range	*SCFH/HR LPG	BTU/H LPG @ 100 PSI Inlet	BTU/H LPG @ 20 PSI Inlet
MEGR-1630-104/78	First Stage Regulator	2" FNPT	1/2"	10	8-20	18,900	47,000,000	7,700,000

*Flow rate at 100 PSIG inlet pressure

MEGR-1630 SPECIFICATIONS:

Type: Adjustable/PSI
 Orifice Diameter: 1/2"
 Orifice Material: Stainless Steel
 Max. Inlet Pressure: 250 PSI
 Regulator Spring: Steel
 Stem Guide/Disk Holder: Stainless Steel
 Valve Stem: Steel
 Exterior Finish: Gray Powder Coat
 Diaphragm: Fabric Reinforced Nitrile (NBR)
 Bonnet Cap & Bonnet / Body Material: Iron

* Other configurations and materials available upon request.



For Your Local Marshall Excelsior Distributor Call 269-789-6700,
 Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com
www.marshallexcelsior.com



Made in the
U.S.A