

Safety Data Sheet

Page 1 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

1. Identification

Product identifier

Trade name: Rislone® Gas Fuel System Cleaner – Right Side
Product code: 44700

Recommended use and restriction on use

Recommended use: Treatment for gasoline.

Restrictions on use: No further relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Rislone
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321



Distributor:

Smits Group Pty Ltd.
50 Radius Drive
Larapinda
QLD 4110
Australia
AUS Telephone 1800 883 888

Emergency telephone number:

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

New Zealand 0800 764 766 (National Poison Control Centre)
Australia 131126 (NSW Poison Control Centre)

2. Hazards identification

Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Tox. 5 H313 May be harmful in contact with skin.
Inh. Tox. 5 H333 May be harmful if inhaled.
Skin Irr. 3 H316 Causes mild skin irritation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

GHS Label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms: Not Regulated

Safety Data Sheet

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side



GHS02 GHS08

Signal word: Danger

Hazard Statements:

- H226 Flammable liquid and vapour.
- H313 May be harmful in contact with skin.
- H333 May be harmful if inhaled.
- H316 Causes mild skin irritation.
- H304 May be fatal if swallowed and enters airways.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces/ No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description:

Other hazards There are no other hazards not otherwise classified that have been identified.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3. Composition and information on ingredients

Chemical characterization: Mixtures

Components:		
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 5, H313	40-50%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	<5%

Safety Data Sheet

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

	<ul style="list-style-type: none"> Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Acute Tox. 5, H313 	
	Polyolefin alkyl phenol alkyl amine	<5%
	Skin Irrit. 2, H315	
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene <ul style="list-style-type: none"> Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401 	<2.5%
CAS: 108-67-8 EINECS: 203-604-4	Mesitylene <ul style="list-style-type: none"> Flam. Liq. 3, H226 Aquatic Chronic 2, H411 STOT SE 3, H335 	<1.1%
CAS: 128-39-2 EINECS: 204-884-0	2,6-di-tert-butylphenol <ul style="list-style-type: none"> Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315 	<1%
CAS: 526-73-8 EINECS: 208-394-8	1,2,3-trimethylbenzene <ul style="list-style-type: none"> Flam. Lq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 STOT SE 3, H335-H336 	<1%
CAS: 98-82-8 EINECS: 202-704-5	Cumene <ul style="list-style-type: none"> Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333 	<1%

Additional information: For the wording of the listed Hazard Statements refer to section 16.

4. First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Safety Data Sheet

Page 4 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

See medical treatment in case of complaints.

After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while lying on their back should be turned onto their side.

Most important symptoms and effects, both acute and delayed:

Coughing

Dizziness

Breathing difficulty

Gastric or intestinal disorders

May be harmful in contact with skin

May be harmful if inhaled

Causes mild skin irritation

Hazards: Danger of impaired breathing.

Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Foam

Alcohol resistant foam

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

Water haze or fog

For safety reasons unsuitable extinguishing agents:

Water with full jet

Water spray

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water fog or haze.

Use large quantities of foam as it is partially destroyed by the product.

6. Accidental release measures

Safety Data Sheet

Page 5 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Prevent from spreading (e.g., by damming in-or oil barriers).

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Remove from the water surface (e.g., skim or suck off).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. Handling and storage

Handling:

Precautions for safe handling

Keep out of reach of children.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Avoid breathing mist/vapours/spray.

Avoid contact with the eyes and skin.

Information about fire - and explosion protection:

Keep respiratory protective device available.

Keep ignition sources away – Do not smoke.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Specific end use(s) No further relevant information available.

8. Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene

Safety Data Sheet

Page 6 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

REL (USA) TLV (USA)	Long-term value: 125 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
108-67-8 mesitylene	
REL (USA) TLV (USA)	Long-term value: 125 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
526-73-8 1,2,3-trymethylbenzene	
REL (USA) TLV (USA)	Long-term value: 125 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
98-82-8 Cumene	
WES (Australia)	Short-term value: 375 mg/m ³ , 75 ppm Long-term value: 125 mg/m ³ , 25 ppm Sk
PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m ³ , (50) NIC-1 ppm NIC-A3
WES (New Zealand)	Short-term value: 375 mg/m ³ , 75 ppm Long-term value: 125 mg/m ³ , 25 ppm Skin

Exposure controls

Engineering controls: Use only in a well-ventilated area.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases/fumes/aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Eye protection:



Safety glasses

Body protection: Protective work clothing.

Limitation and supervision of exposure into the environment:

No further relevant information available.

Risk management measures: No further relevant information available.

Safety Data Sheet

Page 7 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

9. Physical and chemical properties

Information on basic physical and chemical properties

General information

Appearance	
Form	Liquid
Colour	Light yellow
Odour	Petroleum-like
Odour threshold	Not determined.
Change in condition	
Melting point/Melting range	Not determined.
Boiling point/Boiling range	>35°C (>95°F)
Flammability (solid, gaseous)	Not applicable.
Explosive properties	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits	
Lower	Not determined.
Upper	Not determined.
Oxidising properties	Non-oxidising.
Flash point	40.6°C (105.1°F)
Auto/Self-ignition temperature	Not determined.
Decomposition temperature	Not determined.
pH-value	Not determined.
Viscosity	
Dynamic	Not determined.
Kinematic @ 40°C (104°F)	1.4 mm ² /s
Solubility in/Miscibility with water	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water) at 20°C	Not determined.
Vapour pressure	Not determined.
Density	
Relative density	0.77
Vapour density	Not determined.
Evaporation rate	Not determined.
Particle characteristics	Not determined.
Other information	No further relevant information available.

10. Stability and Reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Safety Data Sheet

Page 8 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

Possibility of hazardous reactions

Flammable liquid and vapour.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Reacts with oxidising agents.

Conditions to avoid Excessive heat.

Incompatible materials Oxidisers.

Hazardous decomposition products Carbon monoxide and carbon dioxide

11. Toxicological information

Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: None

Primary irritant effect:

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

IARC (International Agency for Research on Cancer)		
Present in trace quantities: all except 98-82-8.		
98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	Acetaldehyde	2B
75-56-9	Propylene oxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	Styrene	2B

Probable routes of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

12. Ecological information

Toxicity

Aquatic toxicity:
128-39-2 2,6-di-tert-butylphenol

Safety Data Sheet

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

LC50	0.89 mg/l (Oncorhynchus mykiss)
------	---------------------------------

Persistence and degradability The product is partially biodegradable. Significant residuals remain.

Bioaccumulative potential Does not accumulate in organisms.

Mobility in soil No further relevant information available.

Ecotoxicity No further relevant information available.

Remark: Due to mechanical actions of the product (e.g., agglutinations), damages may occur.

Additional ecological information:

General notes: Avoid transfer to the environment.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13. Disposal considerations

Waste treatment methods

Recommendation



Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. Transport information





UN-Number	
DOT	NA1993
ADR/RID/ADN, IMDG, IATA	UN1268
UN proper shipping name	
DOT	Combustible liquid, n.o.s. (petroleum distillates)
ADR/RID/ADN, IMDG	PETROLEUM PRODUCTS, N.O.S.
IATA	Petroleum products, n.o.s.
Transport hazard class(es)	
DOT	
	
Class	3
Label	3
ADR/RID/ADN	
	

Safety Data Sheet

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

Class	3 (F1)
Label	3
IMDG, IATA	
	
Class	3
Label	3
Packing group	III
DOT, ADR/RID/ADN, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, S-E
Transport in bulk according to Annex II of Marpol and the IBC Code	Not Applicable
Transport/Additional Information:	
DOT	Classified as combustible under US DOT regulations. Labelling is only required for single packages 119 US gal/450 L.
ADR/RID/ADN	
	
Limited Quantity for packages less than 30 kg gross and inner packagings less than 5L each.	
IMDG	
	
Limited Quantity for packages less than 30 kg gross and inner packagings less than 5L each.	
IATA	
	
Limited Quantity for packages less than 30 kg gross and inner packagings less than 5L each/10L net.	

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

IARC (International Agency for Research on Cancer)		
Present in trace quantities: all except 98-82-8.		
98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	Acetaldehyde	2B
75-56-9	Propylene oxide	2B

Safety Data Sheet

Page 11 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	Styrene	2B
110-00-9	Furan	2B

Australia

Australian Inventory of Chemical Substances	
All ingredients are listed or exempt.	
Standards for the Uniform Scheduling of Medicines and Poisons	
Hydrocarbon Liquids	S5

New Zealand HSR002584

New Zealand Inventory of Chemicals (NZIOC)
All ingredients are listed or exempt.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation of latest revision of SDS

December 13, 2022: Revised SDS to comply with The Model Work Health and Safety Regulation, and the Globally Harmonized System of Classification and Labelling of Chemicals 7th Revised Edition.

Relevant phrases

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H303 May be harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H313 May be harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H333 May be harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances

Safety Data Sheet

Page 12 of 12

According to The Model Work Health and Safety Regulations, and the
Globally Harmonized System of Classification and Labelling of
Chemicals 7th Revised Edition

Revision: 13 December 2022

Trade Name: Rislone® Gas Fuel System Cleaner – Right Side

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bio-accumulable, Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Corr. 3: Skin corrosion/irritation – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/subreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com