

Electric induction range cooker, sealed 6 mm thick glass ceramic hob, pot detection system which activates heating upon presence of cooking receptacles. Appliance constructed in 304 stainless steel.

Equipped with 4 independent cooking zones with 5 kW output, diam. 280 mm. Cooking zones marked with silkscreened circles on the glass-ceramic surface. Control knob for selection of 10 power settings. Indicator LED indicating activation of heating and correct appliance operation. Internal power-box, main safety sensor. Appliance equipped with height adjustable feet in stainless steel. IPX5 protection rating.

#### STANDARD FEATURES

- Heavy Duty 2mm thick pressed tops
- Modular design
- High efficiency induction
- IPX5 water rating
- Easy to clean
- 6mm Sealed glass top
- Safety cut-off
- Hygiene valve collar on all front controls

#### OPTIONAL FEATURES

- Cabinet base
- Hygenic cabinet base
- Stand base
- Castors

#### DIMENSIONS

External: 930D x 800W x 230H mm

#### TECHNICAL DATA

Power Supply: 415 VAC-3NE 50Hz

Total Output: 20kW

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

ANI98TE

90 SERIES 800MM WIDE INDUCTION TOP

