

TECHNICAL DATA SHEET – ANGEL OF WATER CM-1 – COLON IRRIGATION DEVICE

The Angel of Water CM-1 Surround, a Class II Medical Device, is for colon irrigation when medically indicated, such as before radiological or endoscopic examination. It is a Type B Applied Part and is ME equipment compliant with IEC 60601-1 requirements.

IEC 60601-1:1988 + A1:1991 + A2:1995

EN 60601-1 (2006/A11: 2011) Medical electrical equipment – Part 1: General requirements for basic safety and essential performance and IEC 60601-1, ed. 3, 2005 Medical electrical equipment – Part 1: General requirements for basic safety and essential performance

ELECTRICAL RATINGS

110-120 Vac 60 Hz unit is rated for 2A (U.S., Canada) 220-240 Vac 50/60 Hz unit is rated for 1A (EU, Asia)

UV LIGHT

The Angel of Water CM-1 comes with a UV Light/Sediment Filter; germicidal 254 nm; rated for 7,500 hours of continuous use or 24 months of intermittent use

FILTERS

Pre-Filter: Per Manufacturer's Instructions Sediment: Rated at 16,000 gallons or 4 months

FLOW RATE

Gravity only; averages 1 p.s.i.; averages 1 liter per minute of flow

LIGHT BULBS (Compact Fluorescent ONLY)

View tube: Rated at 10,000 hours Tower: Rated at 8,000 hours

Patient Weight Limit: 400 lbs.

Environmental

Temperature:

Relative Humidity:

Operating 0-75% (non-condensing)
Storage 0-75% (non-condensing)
Transport 0-95% (non-condensing)

Atmospheric Pressure:

 Operating
 700 hPa to 1060 hPa

 Storage
 700 hPa to 1060 hPa

Altitude:

Operating a ≤ 3000 m

Dimensions

Length 101"/256.5cm Width 32.5"/82.6cm

Height 43"/109.2cm (top of basin cabinet); 67"/170.2cm (top of tower cabinet)

Weight 450 lbs. (approximate)

