


The **PowerCharge™ Energy Series** is designed to be the ultimate electric vehicle charging solution. An attractive, powerful, and durable level 2 charger, the **PowerCharge™ Energy Series** features...

- ✓ A slim and durable design that is outdoor rated\* and mounts discreetly in your garage or at your parking space with a simple plug-in installation (or hardware installation for outdoors).
- ✓ The *Energy Series* has a footprint smaller than an 8.5" x 11" sheet of paper.
- ✓ At up to 6x faster than your standard 110v plug, the *Energy Series* safely delivers up to 25 miles of range to your EV for every hour of charge time.
- ✓ With our adjustable power output, you can have the ideal power to match your supply panel, electric vehicle, and driving range.
- ✓ We back up our *Energy Series* with a 3-year warranty (5-year warranty available)
- ✓  The charger is UL-listed and meets safety criteria for use throughout North America.




## Models & Configurations

### Models



#### Energy

Open access version, popular for residential and fleet use.

- Powerful 7.6kW output, adjustable to 5.8kW or 3.8kW
- 25' cable standard
- Easy plug-in installation or hardwire for outdoor install
- 3-year warranty, 5-year optional
- Safety certified 
- Slim, attractive design
- All-weather durability
- Level 2 AC, single port  
*(dual port pedestal available)*

#### Energy Connect

With the help of the **PowerCharge™** app, controlling and monitoring your charger is as simple as pushing a button.

Visit the App Store to download the **PowerCharge™ Energy** app today.

- All of the same great features of the *Energy* model plus:
  - Easy remote management
  - Track energy consumed
  - Schedule charge time
  - Monitor status
  - Remote on/off

### Configurations

#### Single-Port Pedestal



#### Dual-Port Pedestal



#### Wall Mount



## Technical Specifications

Item	E20-SWE	E20-SWC
Application	Residential/Light Commercial	
Voltage (Vac)	208/240VAC, Single Phase	
Frequency (Hz)	60 Hz	
Current (Rms)	Adjustable 16A/24A/32A (3.8kW/5.8kW/7.6kW)	
Circuit Breaker	16A=20A/24A=30A/32A=40A	
Charging Connector	SAE J1772	
Charging Cable Length	25 ft.	
Metering Accuracy	N/A	Embedded $\pm 3\%$
Real Time Clock	N/A	Yes (7 days)
Wi-Fi	N/A	802.11 b/g/n
Display	N/A	116(L)*8.5(W)*37(H)mm, 5.57mm CHARACTER HEIGHT, 5*8 DOT MATRIX, OLED 20x2
Data Protocol	N/A	OCPP 1.6
Operation Temperature	-30C/-22F to 50C/122F	
Storage Temperature	-40C/-40F to 70C/158F	
Mounting Type	Wall Mount / Pedestal Mount (optional)	
Wiring Type	Plug-In (NEMA 6-50) or Hard-wired	
IP Performance	NEMA 4	
Impact Resistance	IK10	
Dimension (HxWxH, inches)	11.14" x 7.56" x 3.11"	
Web Portal Management	N/A	Yes
Console Management	Yes	
Certification	UL 50/991/1449/1998/2231/2594 FCC Part 15B	
	N/A	FCC Part 15.225 (RFID 13.56MHz)
Console Management	Yes	
Warranty	3-year warranty (5-year available)	