## STONE SOAP CO., INC

# Safety Data Sheet Foam It White Tire Cleaner

## **SECTION 1: Identification**

#### 1.1 Product identifier

Product name Foam It White Tire Cleaner

Product number AW-051, 052, 053, 055

Brand Stone Soap

Substance name Automotive Tire Cleaner

1.4 Supplier's details

Name Stone Soap Co., Inc Address 2000 Pontiac Dr.

Sylvan Lake, MI 48320

US

Telephone 248-706-1000 Fax 248-706-1001

email sales@stonesoap.com

1.5 Emergency phone number(s)

Chemtrec 1-800-424-9300

#### **SECTION 2: Hazard identification**

## 2.1 Classification of the substance or mixture

- Acute toxicity, dermal (chapter 3.1), Cat. 3
- Eye damage/irritation (chapter 3.3), Cat. 1
- Sensitization, skin (chapter 3.4), Cat. 1B
- Acute toxicity, oral (chapter 3.1), Cat. 4

#### 2.2 GHS label elements, including precautionary statements

### **Pictogram**



Signal word Warning

Hazard statement(s)

H316 Causes mild skin irritation
H320 Causes eye irritation

H318 Causes serious eye damage
H317 May cause an allergic skin reaction

H302 Harmful if swallowed

Precautionary statement(s)

P264 Wash ... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/.../if you feel unwell,

#### 2.3 Other hazards which do not result in classification

Causes mild skin irritation

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Substance name Automotive Tire Cleaner

#### **Hazardous components**

1. WATER

Concentration 55 - 58 % (Weight)

Other names / synonyms WATER CAS no. 7732-18-5

2. SODIUM XYLENE SULFONATE

Concentration 10 - 12 %

Other names / synonyms SXS; XYLENESULFONIC ACID, SODIUM SALT

CAS no. 1300-72-7

## 3. ETHYLENE GLYCOL MONOBUTYL ETHER

Concentration 5 - 8 %

Other names / synonyms BUTOXYETHANOL; BUTYL CELLOSOLVE

EC no. 203-905-0 CAS no. 111-76-2 Index no. 603-014-00-0

- Acute toxicity (chapter 3.1), Cat. 4

Eye damage/irritation (chapter 3.3), Cat. 2Skin corrosion/irritation (chapter 3.2), Cat. 2

H302 Harmful if swallowed
H312 Harmful in contact with skin
H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

4. Sodium silicate

Concentration 5 - 8 %

Other names / synonyms Sodium silicate; Sodium water glass

CAS no. 1344-09-8

- Skin corrosion/irritation (chapter 3.2), Cat. 1B

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

H314 Causes severe skin burns and eye damage

H335 May cause respiratory irritation

## 5. Proprietary nonionic surfactant blend

Concentration 5 - 7 %

Other names / synonyms Proprietary nonionic surfactant blend

- Acute toxicity, oral (chapter 3.1), Cat. 4

- Skin corrosion/irritation (chapter 3.2), Cat. 1B

- Hazardous to the aquatic environment - acute hazard (chapter 4.1), Cat. 3

- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 4

H302 Harmful if swallowed

H302+H312 Harmful if swallowed or in contact with skin
H314 Causes severe skin burns and eye damage
H410 Very toxic to aquatic life with long lasting effects

#### 6. POTASSIUM HYDROXIDE Solution

Concentration 3 - 6 %

Other names / synonyms CAUSTIC POTASH; KOH

EC no. 215-181-3 CAS no. 1310-58-3 Index no. 019-002-00-8

- Acute toxicity (chapter 3.1), Cat. 4

- Skin corrosion/irritation (chapter 3.2), Cat. 1A

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

7. Sodium tripoly phosphate

Concentration 3 - 5 %

Other names / synonyms Sodium phosphate, tribasic; Sodium tripoly phosphate; STPP

CAS no. 7758-29-4

- Skin corrosion/irritation (chapter 3.2), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2B

H315 Causes skin irritation

H319 Causes serious eye irritation

#### Trade secret statement (OSHA 1910.1200(i))

If Chemical Name/CAS number is "proprietary" and/or weight is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### **SECTION 4: First-aid measures**

#### 4.1 Description of necessary first-aid measures

If inhaled Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Oxygen or artificial respiration may be necessary. Seek medical

attention-if required.

In case of skin contact Wash with large quantity of soap and water. Wash contaminated clothing

before reuse. If skin irritation occurs, seek medical attention.

In case of eye contact Rinse immediately with cool running water, including under eyelids for at

least 15 minutes. Remove contact lenses, if present, after five minutes. continue rinsing eyes. If irritation continues, seek medical attention.

If swallowed DO NOT induce vomiting. Drink one ot two glasses of water. Seek medical

attention immediately.

## 4.2 Most important symptoms/effects, acute and delayed

Direct contact may cause skin or eye irritation. May cause irritation to gastric/intestional mucosa.

## **SECTION 5: Fire-fighting measures**

#### 5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Specific hazards arising from the chemical

None

#### 5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

## 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Handle according to accepted industrial hygene and safety practice. Use personal protective equipment (see section 8). Follow all label directions.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep away from excessive heat or incompatible materials, oxidizers and reducing agents.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### 1. 2-Butoxyethanol (CAS: 111-76-2)

PEL (Inhalation): 50 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

#### 2. 2-Butoxyethanol (CAS: 111-76-2)

PEL (Inhalation): 240 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

## 3. 2-Butoxyethanol (CAS: 111-76-2)

PEL (Inhalation): 20 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

#### 4. 2-Butoxyethanol (CAS: 111-76-2)

REL (Inhalation): 5 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

#### 8.2 Appropriate engineering controls

Use in well ventilated area. Eyewash and emergency showers should be available.

#### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body protection**

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

None required

#### Thermal hazards

None

#### **Environmental exposure controls**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Red or Green Appearance/form Odor Indistinct Odor threshold Not determined рН 12.0-13.0 Melting point/freezing point > 32FInitial boiling point and boiling range > 212FFlash point > 212F Evaporation rate N/A Flammability (solid, gas) N/A Upper/lower flammability limits N/A Upper/lower explosive limits N/A

Vapor pressure Not determined Vapor density Not determined

Relative density 1.05

Solubility(ies) 100% in water
Partition coefficient: n-octanol/water Not determined

Auto-ignition temperatureN/ADecomposition temperatureN/AViscosity30 cstExplosive propertiesNoneOxidizing propertiesNone

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not reactive under normal storage conditions.

#### 10.2 Chemical stability

Stable under normal storage conditions

#### 10.3 Possibility of hazardous reactions

None

#### 10.4 Conditions to avoid

Excessive heat

#### 10.5 Incompatible materials

Strong oxidiers and reducing agents

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2). Carbon monoxide. Oxides of nitrogen. Hydrocarbons.

## **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

SODIUM XYLENE SULFONATE LD50 Oral - Rat - .5000 mg/kg LC50 Skin - Rabbit - 2000 mg/kg

ETHYLENE GLYCOL MONOBUTYL ETHER LD50 Skin - Guinea pig - >2000 mg/kg LD50 Oral - Rat - 1300 mg/kg

Sodium silicate LD50 Oral - Rat - 600 mg/kg

Proprietary nonionic surfactant blend LD50 Oral - Rat - 3980 mg/kg LD50 Skin - Rabbit - 2000 - 2991 mg/kg LC50 Inhalation - Rat - 1.15 mg/l - 4 h

POTASSIUM HYDROXIDE Solution LD50 Oral - Rat - 276 mg/kg Eyes:Result: Major potential hazard Skin:Result: Major potential hazard

Sodium tripoly phosphate
Irritation Unreported - Rat - 3900 mg/kg
Irritation Unreported - Rabbit - 4640 mg/lg

#### Skin corrosion/irritation

Causes moderate to severe skin irritation.

#### Serious eye damage/irritation

Causes moderate to severe eye irritation.

#### Respiratory or skin sensitization

No data available.

## Germ cell mutagenicity

No specific data

#### Carcinogenicity

No known significant effects or critial hazards.

## Reproductive toxicity

No known significant effects or critial hazards.

#### Summary of evaluation of the CMR properties

No known significant effects or critial hazards.

#### STOT-single exposure

No known significant effects or critial hazards.

#### STOT-repeated exposure

No known significant effects or critial hazards.

#### **Aspiration hazard**

No known significant effects or critial hazards.

## **SECTION 12: Ecological information**

#### **Toxicity**

SODIUM XYLENE SULFONATE

EC50 - Daphnia magna (water flea) - 408 mg/kg - 48 h

EC50 - Algae - Selenastrium sp. - 230 mg/l - 96 h

#### ETHYLENE GLYCOL MONOBUTYL ETHER

LC50 - Oncorhynchus mykiss (rainbow trout) - 1474 mg/kg - 96h

EC50 - Daphnia magna (water flea) - 1550 mg/l - 48h

Result: Ethylene glycol monobutyl ether CAS 111-76-2

Partition coefficient: n-octanol/water: log Pow 0.83

#### Sodium silicate

No data

## Proprietary nonionic surfactant blend

LC50 - Pimephales promelas (fathead minnow) - 3.8 - 6.2 mg/l - 96h

LC50 - Daphnia magna (water flea) - 9.3 - 21.4 mg/l - 48h

#### POTASSIUM HYDROXIDE Solution

LC50 - Misquito fish - 80 mg/l - 24h

## Sodium tripoly phosphate

No data

## Persistence and degradability

SODIUM XYLENE SULFONATE

No data

#### ETHYLENE GLYCOL MONOBUTYL ETHER

Remarks: Ethylene glycol monobutyl ether CAS 111-76-2

Biodegradability:aerobic.
Inoculum: activated sludge.
Result: Readily biodegradable

Biodegradation: 90.4% Exposude time: 28 days OECD Test Guideline 301B

Sodium silicate

No data

Proprietary nonionic surfactant blend

No data

POTASSIUM HYDROXIDE Solution

No data

Sodium tripoly phosphate

No data

#### **Bioaccumulative potential**

No data available

#### Mobility in soil

No data available.

#### Results of PBT and vPvB assessment

No data available.

#### Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

#### Disposal of the product

The generation of waste should be avoided or minimized whenever possible. Disposal of this product, solutions and any by-products should at all time comply with the requirements of environmental protection and waste disposal legislation and any regional or local requirements.

#### Disposal of contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## **SECTION 14: Transport information**

DOT (US)

UN Number: Not regulated

**IMDG** 

Not regulated

**IATA** 

Not regulated

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations specific for the product in question

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 311/312 Hazards

No SARA hazards.

## **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **SECTION 16: Other information**

Effective 4/10/15

#### 16.1 Further information/disclaimer

The statements on this SDS are believed to be true and accurate, but because conditions are beyond our control, Stone Soap Co., Inc. does not make, nor does it authorize any agent or representative to make any oral or written warranty, guarantee or representation, expressed or implied, concerning this material or the use thereof beyond the statements on the label. Stone Soap Co., Inc. and the seller disclaim liability for, and expect the buyer to assume all risk for any claim or personal injury or property damage or loss resulting from handling, storage or use of this material not in accordance with the written directions. No other warranty exists.

#### 16.2 Preparation information

Generated by Stone Soap Co., Inc. 2000 Pontiac Dr. Sylvan Lake, MI 48320