STONE SOAP CO., INC

Safety Data Sheet Rainbow Clearcoat / Sealer Wax

SECTION 1: Identification

1.1 Product identifier

	Product name	Rainbow Clearcoat / Sealer Wax
	Product number Brand Substance name	RL-, 904, 905, 906, 907 Stone Soap Automotive Rinse Aid
1.4	Supplier's details	
	Name Address	Stone Soap Co., Inc 2000 Pontiac Dr. Sylvan Lake, MI 48320 US
	Telephone Fax email	248-706-1000 248-706-1001 sales@stonesoap.com

1.5 Emergency phone number(s)

Chemtrec 1-800-424-9300

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

- Eye damage/irritation (chapter 3.3), Cat. 2A
- Skin corrosion/irritation (chapter 3.2), Cat. 3

2.2 GHS label elements, including precautionary statements

Pictogram

 \bigcirc

Signal word

Warning

Hazard statement(s) H319 H316 H315

Causes serious eye irritation Causes mild skin irritation Causes skin irritation

Precautionary statement(s) P264 P280

Wash ... thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P302+P352	IF ON SKIN: Wash with plenty of water/
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.

2.3 Other hazards which do not result in classification Causes mild skin irritation

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Substance name	Automotive Rinse Aid				
Hazardous components					
1. WATER Concentration	60 - 70 % (Weight)				
Other names / synonyms CAS no.	WATER 7732-18-5				
2. Nonionic Concentration	6 - 12 %				
Other names / synonyms	Proprietary				
3. Distallates (petroleum), straight-run middleConcentration4 - 12 %					
Other names / synonyms CAS no.	Distallates (petroleum), straight-run middle 64741-44-2				
4. ETHYLENE GLYCOL MONOBUTYL ETHERConcentration2 - 10 %					
Other names / synonyms EC no. CAS no. Index no.	2-BUTOXY-1-ETHANOL; 2-BUTOXYETHANOL; BUTYL CELLUSOLVE 203-905-0 111-76-2 603-014-00-0				

- Skin corrosion/irritation (chapter 3.2), Cat. 2

H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

5. Proprietary nonionic surfactant blend

Concentration

Other names / synonyms

Proprietary nonionic surfactant blend

- Acute toxicity, oral (chapter 3.1), Cat. 4

- Skin corrosion/irritation (chapter 3.2), Cat. 1B

- Hazardous to the aquatic environment - acute hazard (chapter 4.1), Cat. 3

- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 4

1 - 3 %

H302	Harmful if swallowed
H302+H312	Harmful if swallowed or in contact with skin
H314	Causes severe skin burns and eye damage
H410	Very toxic to aquatic life with long lasting effects

Trade secret statement (OSHA 1910.1200(i))

If Chemical Name/CAS number is "proprietary" and/or weight is listed as a range, the specific chemical identity and/or percentage of composition has been withheld a s a trade secret.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration may be necessary. Seek medical attention-if required.
In case of skin contact	Wash with large quantity of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs, seek medical attention.
In case of eye contact	Rinse immediately with cool running water, including under eyelids for at least 15 minutes. Remove contact lenses, if present, after five minutes. continue rinsing eyes. If irritation continues, seek medical attention.
If swallowed	DO NOT induce vomiting. Drink one ot two glasses of water. Seek medical attention immediately.

4.2 Most important symptoms/effects, acute and delayed

Headache, nausea or dizziness. Direct contact may cause skin or eye irritation.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- 5.2 Specific hazards arising from the chemical None
- **5.3 Special protective actions for fire-fighters** Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Handle according to accepted industrial hygene and safety practice. Use personal protective equipment (see section 8). Follow all label directions.

7.2 Conditions for safe storage, including any incompatibilities Keep away from excessive heat or incompatible materials, oxidizers and reducing agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. 2-Butoxyethanol (CAS: 111-76-2) PEL (Inhalation): 50 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

2. 2-Butoxyethanol (CAS: 111-76-2) PEL (Inhalation): 240 mg/m3 (OSHA) OSHA Annotated Table Z-1, www.osha.gov

3. 2-Butoxyethanol (CAS: 111-76-2) PEL (Inhalation): 20 ppm (Cal/OSHA) OSHA Annotated Table Z-1, www.osha.gov

4. 2-Butoxyethanol (CAS: 111-76-2) REL (Inhalation): 5 ppm (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

Use in well ventilated area. Eyewash and emergency showers should be available.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

None required

Thermal hazards

None

Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

SECTION 10: Stability and reactivity

10.1 Reactivity

Not reactive under normal storage conditions.

- **10.2 Chemical stability** Stable under normal storage conditions
- 10.3 Possibility of hazardous reactions None
- **10.4 Conditions to avoid** Excessive heat
- **10.5 Incompatible materials** Strong oxidiers and reducing agents
- **10.6 Hazardous decomposition products** Carbon dioxide (CO2). Carbon monoxide. Oxides of nitrogen. Hydrocarbons.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity Nonionic (Proprietary) Oral LD50 = 620mg/kg (Rat) Dermal LD50 = 10g/kg (Rat)

Ethylene glycol monobutyl ether CAS 111-76-2 Oral LD50 =500mg/kg estimate based upon calculation method Inhalation = 4500 ppm estimate based upon calculation method Dermal LD50 = 1100mg/kg estimate based upon calculation method

Distallates (petroleum), straight-run middle CAS 64741-44-2 Oral LD50 (Rat) >2000mg/kg Dermal LD50 (Rabbit) >5000mg/kg

Proprietary nonionic surfactant blend LD50 Oral - Rat - 3980 mg/kg LD50 Skin - Rabbit - 2000 - 2991 mg/kg LC50 Inhalation - Rat - 1.15 mg/l - 4 h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes moderate to severe eye irritation.

Respiratory or skin sensitization No data available.

Germ cell mutagenicity No specific data

Carcinogenicity

No known significant effects or critial hazards.

Reproductive toxicity

No known significant effects or critial hazards.

Summary of evaluation of the CMR properties

No known significant effects or critial hazards.

STOT-single exposure

No known significant effects or critial hazards.

STOT-repeated exposure

No known significant effects or critial hazards.

Aspiration hazard

No known significant effects or critial hazards.

SECTION 12: Ecological information

Toxicity

Nonionic (Proprietary)

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Ethylene glycol monobutyl ether CAS 111-76-2

EC50 =1800mg/I Daphina magna (water flea) 48 hours OECD TEst Guideline 202

LC50 =1474mg/l Oncorhychus mykiss 96 hours OECD TEst Guideline 203

EC50 =911mg/l Pseudokirchneriella subcapitata (green algae) 72 hours OECD TEst Guideline 201

Distallates (petroleum), straight-run middle CAS 64741-44-2 Not available

Proprietary nonionic surfactant blend LC50 - Pimephales promelas (fathead minnow) - 3.8 - 6.2 mg/l - 96 h LC50 - Daphnia magna (water flea) - 9.3 - 21.4 mg/l - 48 h

Persistence and degradability

Nonionic (proprietary) Not Determined

Ethylene glycol monobutyl ether CAS 111-76-2 Biodegradability:aerobic. Inoculum: activated sludge. Result: Readily biodegradable Biodegradation: 90.4% Exposude time: 28 days OECD Test Guideline 301B

Distallates (petroleum), straight-run middle CAS 64741-44-2 Biodegradability: Inherent

Proprietary nonionic surfactant blend ^0% biodegradation, 28 d, OECD 301B

Partition coefficient, n-octanol/water (log Pow) - 2.1 - 3.4 - Calculated

Bioaccumulative potential

Nonionic (proprietary) Not Determined

Ethylene glycol monobutyl ether CAS 111-76-2 Partition coefficient: n-octanol/water: log Pow: 0.83

Distallates (petroleum), straight-run middle CAS 64741-44-2 Not available

Proprietary nonionic surfactant blend Partition coefficient, n-octanol/water (log Pow) - 2.1 - 3.4 - Calculated

Mobility in soil Nonionic (proprietary) Not Determined

Ethylene glycol monobutyl ether CAS 111-76-2 No data available

Distallates (petroleum), straight-run middle CAS 64741-44-2 Not available

Proprietary nonionic surfactant blend No relevant data

SECTION 13: Disposal considerations

Disposal of the product

The generation of waste should be avoided or minimized whenever possible. Disposal of this product, solutions and any by-products should at all time comply with the requirements of environmental protection and waste disposal legislation and any regional or local requirements.

Disposal of contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14: Transport information

DOT (US)

UN Number: Not regulated

IMDG Not regulated

IATA Not regulated

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Toxic Substances Control Act (TSCA) Inventory

Ethylene glycol monobutyl ether CAS 111-76-2 and Nonyl phenolpolyethylene glycol ether this material is listed or exempted, Distallates (petroleum), straight-run middle CAS 64741-44-2

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards

The following components are subject to reporting levels established by SARA Title III, Section 311/312: Ethylene glycol monobutyl ether CAS 111-76-2, Distallates (petroleum), straight-run middle CAS 64741-44-2, Nonyl phenolpolyethylene glycol ether

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313: Ethylene glycol monobutyl ether CAS 111-76-2, Distallates (petroleum), straight-run middle CAS 64741-44-2

SECTION 16: Other information

Effective 4/10/15

16.1 Further information/disclaimer

The statements on this SDS are believed to be true and accurate, but because conditions are beyond our control, Stone Soap Co., Inc. does not make, nor does it authorize any agent or representative to make any oral or written warranty, guarantee or representation, expressed or implied, concerning this material or the use thereof beyond the statements on the label. Stone Soap Co., Inc. and the seller disclaim liability for, and expect the buyer to assume all risk for any claim or personal injury or property damage or loss resulting from handling, storage or use of this material not in accordance with the written directions. No other warranty exists.

16.2 Preparation information

Generated by Stone Soap Co., Inc. 2000 Pontiac Dr. Sylvan Lake, MI 48320