

Cross Reference Chart: *Single-Pin Scopes to Pro-Light DX2 Kits P/N*

For Not Listed Scopes or Questions- Call Office: 866.586.7305 or email: Larry@LPArcherProducts.com

***FOR A SCOPE WITH BLUE FIBER LIT FROM THE SIDE OF THE FIBER (NOT A PIPED-IN-INSTALL)-
ORDER UV PURPLE SIGHT PIN LIGHT, P/N PLA-832-UV, PLA-428-UV ETC. IN KIT OR SEPARATELY.**

****MAX Pin Fiber Brightness (Especially Blue) Requires Piping Light Down Fiber to Pin End, & Flaring Both Ends Of Fiber.**

SCOPE BRAND	MODEL-VERSION	Misc. Info.	PLDX2 Kit(s) -XXX
		Recommended modifications are the responsibility of the end user, and LP Archery Products is not held liable unless LPAP does them.	-10B = .010 Blue Fiber -15G = .015 Green Fiber -19R = .019 Red Fiber, Etc.
Axcel	X31, X41, AV25, AV31, AV41	Must use Axcel "Y or T" Yoke windage rod & Axcel sight bar w/ kits listed. Or order separately PLA-AXL-FT & PLA-332-HO Sight Pin Light.	PLK2-AXL-10x, 15x, 19x
B3 Archery	2020 & Newer	Use 8-32 Kit w/ threaded black tip. Or 8-32 UV SPL for dot on lens.	PLK2-832-10x, -19x, 29x
Bowfinger	20/20	Use 8-32 Kit w/ threaded black tip. Or 8-32 UV SPL for dot on lens.	PLK2-832-10x, -15x, -19x
CBE (VTX)	2020 & Newer	Use 8-32 Kit for piped in Max Brightness install, especially w/blue fiber. Use 3/8-24 Kit for easier install w/ threaded scope tube, & non-blue fiber.	PLK2-832-10x, 15x, 19x PLK2-332-XXX (+) PLA-3824-ADP
CBE (For Engage or Tek-Hybrid Sights, See Multi-Pin chart)	2005 - 2019	Can have short or long (wrapped around scope in tubing) fiber setup, in up or down pin setup, in any color fiber. (See Kit instructions).	PLK2-832-10x, -19x
	2004 and older	Requires adding an 8-32 tapped hole to beam light onto Green, Red or Yellow fiber/pin. Blue fiber will light up, but Not very bright, with this scope.	PLK2-832UV-VNB
Classic Archery	Magnum, w/Fiber Guard Large, w/ Fiber Guard	Requires Classic's Hooded Fiber Guard +8-32 hole added. Without Hooded Fiber Guard an 8-32 tapped hole must be added to scope, call for details.	PLK2-832-10x, -19x
Copper John	MaXXis	Best w/.094 tubing wrapped around housing into 8-32 SPL, w/Blade Pin.	PLK2-832-10x, -19x
CR (APEX)	A3DSH & Target	Recommend, 8-32 Razor Fire (Blade) Pin; or SS-Tube pin w/ .086 fiber tube.	PLK2-832-10x, -15x, -19x
Davis (Scopes)	The System	Can work with Blade Pin or S.S. Curved Tube Pin (but some fiber tube is smaller and fits loose in our Sight Pin Light (.094" Dia. tip hole).	PLK2-832-10x, -19x
Extreme Archery	2013 & Newer	Recommend using 8-32 Razor Fire Blade or Laser Pin	PLK2-832-10x, -19x
	2010-2012	No good/easy Blue fiber configuration	
	2005-2010	Recommend using 8-32 Razor Fire Blade or Laser Pin	
	2004 & Older	Difficult to setup Blue Sight Pin color, or can't use scope lens	
HTM	2006 & Newer	Can have up/down Pin using a wrap-around install; see install instructs.	PLK2-832-10x, -19x
Shrewd (Prec. Archery)	Optum, Nomad All; 3DXL (2007' w/ 8-32 holes)	Nomad & 3DXL scopes can use/may require; p/n STT-03-094 & p/n PLA-832-TAD, or p/n PLA-832-TAK; both included in DX2 Kit. Optum scopes use 8-32 DX2 kit w/ or w/o threaded black tip; Or can use 8-32 UV Kit or SPL for dot on lens, or lighting fiber from side (not piped in).	PLK2-832-10x, -15x, -19x PLK2-832UV-VNB, -VMB
	3DXL (2006 w/o tapped top/bottom hole)	Needs an 8-32 tapped hole added to scope's top or bottom.	
Spot Hogg	Various (Non Blue fiber) Spark	For Blue Fiber set-ups contact LPA for modifications required. Creates a Blue color crosshair, may not be bright under all conditions.	PLK2-332HO-VNF PLK2-332HO-VNF + PLA-1428-ADP
Sure-LOC	Black Eagle Scope 42 mm, 35mm, 29 mm	Scope must have top/bottom hole for .086 dia. tubing; already added in newer scopes. Tubing included in kits or can be purchased separately; LPA p/n STC-03-086.	PLK2-832-10x, -19x
	S2 Scope w/ S2 Sight Bar S2 Scope w/ S2 Sight Bar S2 Scope w/o S2 Sight Bar	For Green, Red, Yellow fibers. Using the windage rod light threads. For Blue Fiber, (not rcm'd. set-up), may not be bright enough all conditions. NO Clean or rcm'd set-up. Requires rigging tubing into scope fiber wrap.	PLK2-332-HO w/ ¼-28 Adaptor PLK2-332-UV w/ ¼-28 Adaptor PLK2-832-xxx, call for info.
Sword (Non-Blue-Fiber)	Varies	For Blue Fiber set-ups contact LPA for modifications required. For non-blue fiber use with existing tapped hole (3/8-32 or ¼-28 SPL), verify size.	PLK2-428XX-VNB or -VMB PLK2-332-VNB w/ PLA-1428-ADP
Viper (Archery Products)	2006 & newer	Up Pin doable; BUT Requires drilling/modifying Viper Brass SS Pin, and drilling larger thru hole in bottom of scope. See instructions/contact LPA.	PLK2-832-10x, -15x, -19x
	2005	Up/Dwn. pin setup doable w/ Viper SS Pin. See install instructions.	PLK2-832-10x, -15x, -19x
	2004 & older	Requires adding an 8-32 tapped hole to beam light onto Green, Red or Yellow fiber/pin. Blue fiber will light up, but Not very bright, with this scope.	PLK2-832UV-VNB