

TSC

The Smarter Choice.

CELEBRATING 20 YEARS



KP-200 PLUS, KU-007 PLUS – Accessory SIMPLE AND EASY STAND-ALONE LABEL PRINTING SOLUTION



KP-200 PLUS KEY FEATURES

- Portable terminal input device requiring no external power supply
- Easy implementation of stand-alone printing applications
- Additional serial port for connection of input devices
- Optional keypad membrane

KU-007 PLUS KEY FEATURES

- 2 MB Flash and 256 KB SRAM memory
- LCD display panel (graphic type)
- Built-in BASIC-like language interpreter
- Real-time-clock
- Password locking for security
- Built-in EURO currency logo
- 6-digit floating-point calculation
- Optional keypad membrane

APPLICATIONS

- Retail
- Transportation
- Manufacturing
- Healthcare
- Logistics
- Entertainment & Hospitality
- Government
- Postal/ Parcel
- Custom Signage

KP-200 PLUS, KU-007 PLUS – Accessory

KEYBOARD MODEL	KP-200 PLUS
Keyboard	68 keys, large keypad layout
LCD	20 characters x 2 lines
Memory	N/A
Serial interface	COM1: 9 pins, baud rate 9600 bps, male Dsub with cable COM2: 9 pins, baud rate 4800 bps, female Dsub
Power	Input: DC 5V, 250mA
Physical dimension	261 mm (W) x 31 mm (H) x 142 mm (D) 10.2" (W) x 1.2" (H) x 5.6" (D)
Weight	0.6 kg (1.32 lbs)
Environment condition	Operation: 5 ~ 40°C, 20 ~ 80% RH non-condensing Storage: -20 ~ 60°C, 10~ 90% RH non-condensing
Limited warranty	12 months
KEYBOARD MODEL	KU-007 PLUS
Keyboard	68 keys, large keypad layout
LCD	Graphics type with back light
Memory	2 MB Flash, 256 KB SRAM
Serial interface	COM1: 9 pins, baud rate adjustable from 2400 to 19200 bps, male Dsub with cable COM2: 9 pins, baud rate adjustable from 2400 to 19200 bps, female Dsub
Command set	BASIC-like language interpreter
Real time clock	Standard
Power	Input: DC 5V, 250mA
Physical dimension	261 mm (W) x 31 mm (H) x 142 mm (D) 10.2" (W) x 1.2" (H) x 5.6" (D)
Weight	0.6 kg (1.32 lbs)
Environment condition	Operation: 5 ~ 40°C, 20 ~ 80% RH non-condensing Storage: -20 ~ 60°C, 10~ 90% RH non-condensing
Limited warranty	12 months



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 2218 6789
E-mail: printer_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: printer_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Corporate Office
Tel: +1 909 525 9779
E-mail: sales@tscprinters.com

Orlando Office

Tel: +1 407 704 8918
E-mail: sales@tscprinters.com

CANADA

TSC Auto ID Technology America Inc.
Tel: +1 909 525 9779
E-mail: sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +52 (33) 3836 6682
E-mail: sales@idc-componentes.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 9597 8098
E-mail: sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 00
E-mail: info@tsceu.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 915 422 8889
E-mail: info@tsceu.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: info@tscmea.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: printer_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: sale@tscprinters.com.cn

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2013 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.