










SPECIFICATIONS

Model Name	GeForce RTX [™] 4070 VENTUS 2X E 12G OC
Graphics Processing Unit	NVIDIA [®] GeForce RTX [™] 4070
Cores	5888 Units
Memory	12GB GDDR6X
Power connectors	8-pin x 1
Bus Standard	PCI Express [®] Gen 4
Memory Interface	192-bit
Core Clocks	Extreme Performance: 2520 MHz (MSI Center) Boost: 2505 MHz
Memory Speed	21 Gbps
Maximum Displays	4
Digital Maximum Resolution	7680 x 4320
HDCP Support	<u>Y</u>
Power consumption (W)	200 W
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI [™] 2.1a)
Recommended Power Supply (W)	650 W
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Card Dimension(mm)	242 x 125 x 43 mm
Weight	663 g / 959 g

CONNECTIONS



FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.

Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.

Core Pipe



Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.

Reinforcing Backplate



The reinforcing backplate features a flow-through design that provides additional ventilation.

🛐 Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.

© 2023 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2023 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.