

QUICK REFERENCE GUIDE

Problem: Scooter will not switch on	
Symptoms:	Remedy:
Batteries not connected	Check batteries connected
Circuit breaker has tripped	Push circuit breaker to reset

Problem: Scooter will switch on but will not run	
Symptoms:	Remedy:
Flat batteries	Recharge battery
Charger plugged in	Unplug charger from scooter
Motor in freewheel mode	Push down freewheel lever

Problem: Scooter appears slow	
Symptoms:	Remedy:
Flat batteries	Recharge battery
Speed setting slow	Turn up speed dial

Problem: Seat moves whilst in use	
Symptoms:	Remedy:
Seat not locked in position	Slowly rotate the seat until it drops in place and is secure.

Problem: Tiller appears loose or will not swivel freely	
Symptoms:	Remedy:
Tiller adjustment knob loose	Tighten tiller adjustment knob
Tiller Lock Applied	Release Tiller Lock

Problem: Horn sounds involuntarily / automatically	
Symptoms:	Remedy:
The scooter has diagnosed a fault	Ensure the wigwag paddle is released and switch the scooter off and on. Recharge batteries if error persists.

If the scooter has diagnosed a fault the speed display will flash and the horn will beep in sequence. If this occurs, count the number of flashes and refer to the table below.

1. **Low Battery.** Charge batteries as soon as possible.
2. **Low Battery Voltage.** As above
3. **High Battery Voltage.** Remove charger if plugged into the scooter.
4. **Current Time-Out.** The scooter has drawn too much power for too long. Switch off and restart after 5 minutes.
5. **Brake Fault.** Check the freewheel lever is in the DRIVE position
6. **Wigwag Paddle.** Release paddle, switch off the scooter and restart without pressing the paddle.

If any other errors are shown contact your dealer.

CONTENTS

1. PREFACE
2. SAFETY NOTICE
 - 2.1 Before Driving
 - 2.2 Whilst Driving
 - 2.3 Labelling
 - 2.4 Electromagnetic Interference
3. PARTS INTRODUCTION
4. OPERATION
 - 4.1 Control Panel
 - 4.2 How to Operate Your Scooter
5. DRIVING ON THE ROAD
6. BATTERY CHARGING AND CARE
7. INSPECTION AND MAINTENANCE
 - 7.1 Checks
 - 7.2 Service Record
 - 7.3 Battery Pack and Tyres
 - 7.4 Cleaning
 - 7.5 Storage
 - 7.6 Moving About
8. TROUBLESHOOTING
9. SPECIFICATION
10. WARRANTY
11. APPENDIX: SERVICE RECORD

1. PREFACE AND INTRODUCTION

- Please carefully read this owner's handbook before using the scooter to ensure that you operate the scooter safely. Improper use of the scooter could result in damage, injury or traffic accidents.
- This handbook also advises how to get the most out of your scooter by giving comprehensive operating, assembly and maintenance instructions for the scooter.
- A repair and maintenance record chart and warranty information is included with this handbook. Please keep it in a safe place or with the scooter.
- If someone else uses the scooter make sure that you provide him or her with this handbook for their consideration.
- As designs change some of the illustrations and pictures in the manual may not correspond to the scooters that you purchased. We reserve the right to make design modifications.
- The Cobra scooter has been designed and manufactured to provide a comfortable and secure yet affordable solution for some mobility requirements. It is suitable for mainly road and outdoor use and has a top speed of 8mph. It can be used indoors and on the pavement where the environment permits and when the scooter is set to the indoor speed setting. It is a class 3 scooter as defined by the Road Traffic Act 1988.

2. SAFETY


Before Driving

- The user needs to be familiar with the use and operation of this scooter before driving.
- The scooter may only be driven on the pavement or pedestrian areas at speeds up to 4mph (6.4kph). Use the High / Low button on the lower setting to ensure you do not exceed this speed. The scooter may be driven on single carriage roads with the button set to High. This will allow speeds up to 8mph (12.8kph).
- Be aware of traffic and other road users when crossing or using roads.
- Never ride on motorways or dual carriageways.
- Use extreme caution when driving your scooter in busy areas such as shopping malls.
- Do not drive the scooter under the influence of drink or drugs, or when you are tired. Driving under the influence of alcohol or drugs may be an offence under the Road Traffic Act.
- Be careful when using the scooter in low light.
- Before using the scooter in busy or hazardous environments, familiarise yourself with the operation of the scooter. Practice in an open and safe area which is free from hazards and other people. Reduce your speed to a minimum for your initial practice.
- Practice operating your vehicle

Before using the scooter in busy or potentially dangerous areas, familiarize yourself with the operation of your scooter. Please practice in a wide and open area like a park. In order to avoid accidents with your scooter whilst driving, bear in mind driving motions such as accelerating, braking, turning, reversing and gradients.

1. Reduce your speed to a minimum for your initial practice
2. For safety, ensure somebody accompanies you when driving on the road for the first time
3. Only use the higher speed setting when you are confident that you can easily operate and control your scooter

- The Cobra scooter can only be used by one person at a time. Do not carry passengers on your scooter (including children)
- Maximum user mass (weight capacity)
 - The maximum weight that can be carried is 181kg / 28 stone (including occupant and any goods).
 - Do not use the scooter to carry or haul goods.



Whilst Driving

Do not move your body out of the vehicle whilst moving

- Such action may cause you to lose your balance and risk injury from falling
- Pay attention that your clothing and other garments do not get tangled or caught in the wheels

Do not use your vehicle in the following environments

- On roads with heavy traffic or roads that are muddy, gravelly, bumpy, narrow, snowed over or icy.
- Places where you might get the wheels stuck.
- On canal towpaths which are not guarded by any fence or hedge.
- Do not drive at night or if it is raining heavily, snowing, misty or windy.
- Do not drive your vehicle in an 'S' pattern or make erratic turnings.
- Do not take the scooter onto escalators.
- Under no circumstances should the scooter be used as a seat in a motor vehicle (e.g. cars, buses, trains, etc)

Gradients and Drops

- Do not drive on roads with large drops or potholes. Such drops or potholes may cause damage and/or injury.
- Do not cross wide water gutters where there is a risk of getting the wheels stuck.
- Always use a low speed setting when ascending or descending a gradient.
- Do not drive on gradients steeper than those stated on the diagram overleaf:

Warning


Do not set in freewheel mode when driving on a gradient.

Always re-engage the anti-freewheel device before use. Failure to do so may result in injury.

- To protect your safety, the power will automatically cut off and the electromagnetic (EM) brake will activate while you are driving down gradients over 15°. This will limit the speed to a safe level. Switch the power off and on again to restart your scooter.

Step and Obstacle Climbing

- The scooter is capable of climbing an 80mm (3") obstacle from a stationary start or a 100mm (4") obstacle from a moving start.
- The ground clearance of the scooter is 100mm (4").
- To climb an obstacle when moving, start moving at least 50cm (20") from the obstacle and mount the obstacle head on (not at an angle). However, this method is not recommended as this may cause damage and/or injury.



Warning



Mounting an obstacle at speed will cause a jolt to the scooter which may cause discomfort or injury to the user. If you are in any doubt, do not mount the obstacle whilst moving.

Labelling


- Please carefully read all labels applied to the scooter before driving. For future reference, do not remove them from the scooter. The labels are also shown below:


CAUTION

- To adjust tiller angle, press the paddle and pull the tiller.
- Do not adjust the tiller angle, whilst the scooter is moving
- Always check the tiller is locked in the correct position before using
- Do not lean on the tiller whilst mounting or dismounting from the scooter

Located on tiller

Product Code: **COBRASIL** **WARNING:** REFER TO OPERATORS MANUAL FOR INFORMATION
Serial Number: **EMI**

Drive Medical Ltd (HX5 9JP)  THIS UNIT HAS ACHIEVED 20 V/m EMI TESTING

Maximum User Mass 182kg 

Located on rear

WARNING - RISK OF INJURY

NEVER OPERATE THE FREEWHEEL LEVER WHILST SAT ON THE SCOOTER OR ON A GRADIENT

TO OPERATE THE FREEWHEEL LEVER:
Pull the lever **FIRMLY OUT** to engage **FREEWHEEL** mode
Push the lever **FIRMLY IN** to engage **DRIVE** mode

Located by freewheel lever

CARELESSNESS CAUSES FIRE

DRIVE MEDICAL HX5 9JP

To comply with the Furniture and Furnishings (Fire) (Safety) Regulations: This article does not include a Schedule 3 interliner.

All foams, fillings and composites have been tested to ensure compliance with the relevant ignitability test. All covers and fillings have been tested to ensure that they are cigarette resistant. All covers have been tested to ensure that they are match resistant.

Further details are available
From your retailer.

Located on seat

Electromagnetic Interference

- Scooters may be susceptible to electromagnetic interference (EMI) from sources such as mobile phones, walkie-talkies, TV and radio broadcast stations and amateur radio sets. In some cases, there is a risk this interference may cause involuntary movement of the scooter. The scooter has been tested and passed to withstand interference to a level of 20V per metre.
- Be aware that the above sources may cause involuntary movement due to EMI. Exercise caution whilst using the aforementioned devices and avoid close proximity to TV and Radio broadcast stations.
- The addition of components or accessories may effect the EMI susceptibility of the scooter. Do not fit accessories other than Drive Medical authorised accessories.

3. PARTS INTRODUCTION



4. OPERATION

4.1 Control Panel



4.2 How To Operate Your Scooter

- **Key Ignition.** The key ignition acts as the power switch for the scooter. To switch the power on, turn the key clockwise and control panel should illuminate. To switch the power off, turn the key anticlockwise, after which the control panel should switch off and the key can be removed.



Do not turn the ignition off whilst driving as this will lead to an emergency stop and possible risk of damage or injury.

- **Wigwag Paddle.** The scooter is propelled by the user operating the wigwag paddle at the bottom of the control panel. To move the scooter forward, move the right hand side of the paddle towards the user. To reverse the scooter, move the left hand side of the lever. The further the paddle moves, the faster the scooter will travel. To stop the scooter, release the wigwag paddle and the electromagnetic brake will apply automatically.



Warning

Do not push both left and right hand sides of the wigwag simultaneously. You will not be able to control the scooter.

- **Braking.**
- The electromagnetic brake will stop the scooter when the wigwag paddle is released. The brake is also automatically applied when the scooter is

switched off. In the event of an emergency, the user can stop the scooter by operating the cable brake located on the left hand side of the tiller handlebars.



When on a gradient, never set the vehicle to freewheel mode. The brakes will not be applied.

- **Top Speed Setting.** The top speed of the scooter can be increased by pressing the Hare button, or reduced by pressing the Tortoise button. The top speed is displayed on the control panel. The more segments of the display that are lit, the faster the scooter will go.



Do not adjust the speed setting whilst driving as this could result in loss of control. Do not set the highest speed whilst driving indoors.

- **High / Low Speed Setting.** When the scooter is used indoors or in pedestrian environment (such as on the pavement or in a shopping mall) the Low speed setting should be engaged. When the scooter is used on the road, the high speed setting may be engaged.

To engage the Low Speed Setting, press the bottom half of the button (marked 'L') and this will limit the scooter's top speed to 4mph.

- To engage the High Speed Setting, press the top half of the button (marked 'H') and this will allow the scooter to have an 8mph top speed.



Warning

Always engage the Low Speed setting when travelling indoors or the pavement. This is a legal requirement.

- **Horn Button.** Press the horn button to sound the horn, Release the button to stop the horn.
- **Indicator Buttons.** Use the relevant indicators when making a turn to show your direction of travel. Press the Right or Left Indicator button once to operate the relevant indicators. Press the same button again to stop the indicators.
- **Lights Button.** Press the Lights button once to switch on the lights. Press the button again to switch off the lights.


- **Hazard Warning Button.** Press the Hazard Warning button once to switch on the warning function. Press the button again to switch off the function. When operating the Hazard Warning will flash all of the indicators and sound the horn.
- **Battery Gauge.** The amount of power remaining in the battery is shown by this gauge. A fully charged battery will show all the segments of the gauge lit, and the number of segments lit will reduce as the power decreases.

If the battery gauge flashes but the scooter will still drive, then this indicates low battery power and the batteries should be recharged immediately. If the battery gauge flashes and the scooter will not drive, The LED will flash a number of times then pause. Count the number of flashes to determine the problem, and refer to the troubleshooting guide.

Contact your dealer if the error persists after following the recommendations in the troubleshooting guide.

- **Seat.**

- The seat can rotate 360° and locks in 45° settings. To rotate, lift up the lever (A) located underneath the right hand side of the seat and swivel seat. Release the lever and carry on swivelling the seat until it locks in position.



- You can adjust the amount of legroom on the scooter by sliding the seat back and forth. To slide the seat, lift up the seat sliding handle (B). Then adjust the seat to correct position, release the handle and continue sliding the seat until it locks in position.
- To alter the backrest angle, pull up on the seat recline lever, then adjust the backrest to the required position and release the lever. Please note if nobody is using the backrest when the lever is operated, it will automatically spring the backrest forward to fold the seat.



Attention.

Return the seat to the forward position before driving.

- **Armrest Adjustment.** To adjust the angle of the armrest, first flip up the armrest. Then turn the wheel located underneath the armrest pad to adjust to the armrest angle when lowered in to position.



- **Tiller Adjustment**

The tiller can be adjusted into several positions.

1. Push (or pull) the lever on the scooter tiller to adjust the tiller to the position you require.
2. Release the lever to lock the tiller.

- **Circuit Breaker.** The circuit breaker may trip when the scooter is under excessive load or when travelling on steep inclines. It will be more prone to tripping when the scooter is low on battery charge. Under normal conditions the circuit breaker button will protrude by 2mm - 3mm. If the circuit breaker has tripped the button will protrude by 7mm. To reset the circuit breaker, push the button in and the scooter should operate as normal.



Freewheel Lever

The freewheel lever allows the automatic brake to be disengaged so the scooter can be manually pushed and/or manoeuvred. When in freewheel mode the brakes are not applied so it should not be used when:

1. Somebody is sat on the scooter
2. If the scooter is left unattended
3. When the scooter is on a gradient



Engaged (Drive) Mode:

Push the lever UP completely and the scooter can be driven by the motor.

Freewheel Mode:

Pull the lever DOWN and switch the scooter off. The scooter can now be pushed / moved manually.



Warning

The lever should only be set to FREEWHEEL when on flat ground and unoccupied by the user. Otherwise, there is a risk of damage or injury.

5. DRIVING ON THE ROAD

• Starting and Driving

1. Ensure the seat is installed correctly and in the forwards position.
2. Ensure the tiller and seat are adjusted for a comfortable driving position.
3. Fold down the armrests so you can place your arms on them.
4. Switch the ignition on. If necessary, switch on the headlights.
5. Check the battery indicator to see if there is enough power for your trip. If you have any doubt about the remaining power, please recharge the batteries before departure.
6. Set the speed dial to a setting you are safe and comfortable with.
7. Check the wigwag paddle works correctly.
8. Check the electromagnetic brake works correctly.
9. Ensure it is safe around you before you drive on the street or road. Engage the low speed setting if you are driving on the pavement or indoors.



Attention

1. Do not push both sides of the wigwag paddle simultaneously. This may leave you unable to control your scooter, and could cause damage or injury.
2. Do not switch the ignition off while driving as this will lead to an emergency stop and possible risk of damage or injury.
3. Do not set to the highest speed setting whilst driving indoors.
4. Do not adjust the speed setting whilst driving. A sudden change in speed may cause danger to yourself and others, and may cause damage to your scooter.
5. Do not place magnetic devices near the scooters electrical parts as this could affect the safe operation of the scooter.
6. Be careful while driving in heavy traffic or in crowded areas.
7. Whilst reversing the vehicle, beware of people or objects behind you. When reversing, the scooter will sound an audible warning alarm.

6. BATTERY CHARGING AND CARE

Follow the procedure below:

1. Switch the ignition off.
2. Connect the charger power cord in to the mains socket.
3. Open the charging socket cap on the scooter tiller. Then connect the charger round plug in to the scooter charging socket located on the left hand side of the tiller.
4. Switch the charger on at the mains.
5. Both the charger's red and orange LEDs will be lit when charging commences. The charging duration will be around 12 hours. To ensure optimum performance an 18 hour charge is recommended. We do not recommend the scooter be charged for longer than 24 hours.
6. Both the charger's LEDs will be lit during the charging process. The orange LED will turn green when bulk charging is complete after which the charger trickle charges the batteries. Trickle charging optimises the batteries and is necessary to maintain or improve battery performance.
7. Switch off the charger, disconnect the power cord and round plug from the charger socket on the scooter.



ATTENTION

- If only a red LED is lit on the charger, then the scooter is not connected.
- If no LEDs are lit on the charger, then the charger is not connected to the power or it is defective.
- Please only use a charger supplied with the scooter. You may damage the battery and / or scooter if you use an incorrect charger.
- Always charge the battery to its full capacity every time.
- Do not charge in temperatures below -10°C or above $+50^{\circ}\text{C}$ as the charger may not work efficiently and the batteries may become damaged.



WARNING

- Keep away from flammable objects while charging as it may lead to fire or battery explosion.
- Do not smoke while charging as the battery may release hydrogen gas. Always charge the batteries in a well ventilated environment which is not in direct sunlight. Do not charge in surroundings where it is humid, wet or damp.
- Do not handle the charger, scooter or mains socket with wet hands, as this could lead to electric shock.

Battery Care



1. You should recharge the batteries after each time the scooter is used to ensure maximum battery range. The batteries should be charged at least once a week even if the scooter is not used.
2. After charging or replacing a new battery, drive the scooter for a short period to ensure battery capacity is sufficient.
3. In cold environments, the battery may respond more slowly and range will be reduced.
4. When driving on gradients, the battery gauge will fluctuate. This is a normal occurrence.
5. Battery range is reduced when driving up gradients or on rough terrain, as the scooter uses more power.
6. The batteries should not be charged for more than 24 hours.
7. The batteries are sealed, and so do not need topping up with water.
8. The batteries should be checked periodically for cleanliness. Please refer to the section later in the handbook.

Battery Replacement

It is natural for the battery capacity to reduce with time, even if the battery is charged as directed above. When the battery range is about half of its peak performance we recommend that the batteries are changed. Continuing to use an old battery will result in a rapid reduction in the range of the scooter and can cause excessive wear and tear on other parts of the scooter. It is recommended that batteries are replaced in pairs, and that these are fitted by your dealer.

Removing the Batteries

1. Switch off the scooter at the ignition and remove the seat.
2. Lift up the battery cover (A)
3. Disconnect the black battery connectors (B) and red battery connectors.
4. Remove the velcro straps (C) from the battery and pull the battery out.



Cleaning the Battery

If the batteries are contaminated by water, battery acid, dust or other substances, they will discharge quickly. The batteries supplied with the scooter are sealed and as such are maintenance free with no risk of battery leakage. Please follow the steps below to clean the battery:

1. Remove the batteries following the procedure above.
2. Clean the battery with a clean cloth. If the terminal is covered by white powder, wipe it cleaning using warm water.

7. INSPECTION AND MAINTENANCE

7.1 Checks and Maintenance

Your power scooter is designed for minimal maintenance. However, like any motorized vehicle it requires routine maintenance. To keep your **scooter** for years of trouble-free operation, we recommend you follow the following maintenance checks as scheduled.

Weekly Checking

Check the following items weekly or before driving. If you find anything abnormal contact your Drive Medical Dealer for further inspection or advice.

- **Tiller.** Ensure it is not loose and can turn smoothly
- **Speed control dial.** Ensure it adjusts freely.
- **Wigwag paddle.** Ensure scooter moves when lever is pressed, and stops when lever released.
- **Motor.** Check for any abnormal noise and electromagnetic brakes work correctly.
- **Freewheel Lever.** Ensure it works correctly.
- **Seat.** Ensure it swivels and locks easily.
- **Tyres.** Check tyre tread depth and for any signs of damage such as cracking.

Monthly Checks

Visually inspect the controller harnesses. Make sure that they are not frayed, cut or have any exposed wires.

- Make sure you keep the controller clean whilst protecting it from rain or water. Never hose off your scooter or place it in direct contact with water.
- Keep wheels free from lint, hair, sand and carpet fibres.
- Visually inspect the tyre tread. If less than 1mm (1/32"), please have your tyres replaced by your local dealer.
- All upholstery can be washed with warm water and mild soap. Occasionally check the seat and back for sagging, cuts and tears. Replace if necessary. Do not store your scooter in damp or humid conditions as this will lead to mildew and rapid deterioration of the upholstery parts.

All moving mechanisms will benefit from simple lubrication and inspection. Lubricate using petroleum jelly or light oil. Do not use too much oil, otherwise small drips could stain and damage carpets and furnishings etc. Always perform a general inspection of the tightness of all nuts and bolts.

Semi-Annual Checks



Check the motor brushes. We recommended that your authorized dealer inspects the brushes every six months or sooner if your power scooter is not operating smoothly. If inspection determines excessive wear on the brushes, they must be replaced or motor damage will result.

The brushes should be inspected for wear and colour of the braiding inside the spring. If the braiding is dark brown, red, silver, purple or gold then the brush needs replacing.

Warning! Failure to maintain the brushes could void the power scooter warranty.

To inspect or replace the motor brushes:

1. Unscrew the motor brush caps (by using a screwdriver on the caps shown by the white arrow).
2. Remove the brushes.
3. Inspect the brushes for wear (replace if less than 9mm)
4. Replace the brushes if necessary.



- Inspect the state of the battery terminals every six months. Make sure that they are not corroded and the connections are tight. Periodically apply a thin film of petroleum jelly on the surface of terminals to guard against corrosion.

7.2 Service Record

To ensure your scooter is correctly serviced take it to your Drive Medical dealer for regular servicing. We recommend that scooters are serviced at least annually, and your dealer may charge a fee for this.

A copy of the service record is at the back of this handbook. Copies of the servicing schedule are available from Drive Medical to authorised parties on request.



Even if the scooter has not been used, it should still be serviced annually.

7.3 Battery Pack and Tyres

- For information on the battery pack, please read section 6 on Battery Charging and Care.
- Tyre condition will be affected by how you drive the scooter and what terrain it is driven on.
- The Cobra comes with pneumatic tyres, with a recommended inflation pressure of 26 psi (1.8bar) The tyre pressure should be periodically checked.

7.4 Cleaning

- The scooter should be cleaned periodically, especially if you tend to drive on sand, gravel or in other adverse environments.
- Use a soft, wrung dry cloth to keep your scooter clean and dust free. Use a damp cloth and mild detergent to clean the scooter.



Warning

- Do not use a hose pipe or splash water directly on to the scooter.
- Do not use petrol, solvents or vaporising solutions as these may damage body panels. Do not use wax
- Ensure the charger is unplugged and the scooter switched off before cleaning the scooter.

7.5 Storage

- Ensure the scooter is stored with the seat set in the forward position, the scooter switched off with the battery pack removed and charger disconnected.



Store the scooter in environments which are free from direct sunlight and water or moisture.

7.6 Moving About

1. Switch off the scooter using the ignition key and dismount from the scooter. We also recommend removing the seat and batteries prior to moving.
2. Lift the scooter by the chassis only.
3. For your safety ask for help if required. You will need two or more people when moving or lifting the scooter as a whole.



Never lift the scooter by the bumpers or body panels, as this can cause injury or damage.

8 TROUBLESHOOTING

- The troubleshooting guide is also featured on page 1 of the Owner's Handbook.

Problem: Scooter will not switch on	
Symptoms:	Remedy:
Batteries not connected	Check batteries connected
Circuit breaker has tripped	Push circuit breaker to reset

Problem: Scooter will switch on but will not run	
Symptoms:	Remedy:
Flat batteries	Recharge battery
Charger plugged in	Unplug charger from scooter
Motor in freewheel mode	Push down freewheel lever

Problem: Scooter appears slow	
Symptoms:	Remedy:
Flat batteries	Recharge battery
Speed setting slow	Turn up speed dial

Problem: Seat moves whilst in use	
Symptoms:	Remedy:
Seat not locked in position	Slowly rotate the seat until it drops in place and is secure.

Problem: Horn sounds involuntarily / automatically	
Symptoms:	Remedy:
The scooter has diagnosed a fault	Ensure the wigwag paddle is released and switch the scooter off and on. Recharge batteries if error persists.

If the scooter has diagnosed a fault the speed display will flash and the horn beep in sequence. If this occurs, count the number of flashes and refer to the table below.

- Low Battery.** Charge batteries as soon as possible.
- Low Battery Voltage.** As above
- High Battery Voltage.** Remove charger if plugged into the scooter.
- Current Time-Out.** The scooter has drawn too much power for too long. Switch switch off and restart after 5 minutes.
- Brake Fault.** Check the freewheel lever is in the DRIVE position
- Wigwag Paddle.** Release paddle, switch off the scooter and restart without pressing the paddle.

If any other errors are shown contact your dealer.

9 SPECIFICATION

Model Reference	Cobra
Dimension (L x W x H)	160cm x 73cm x 135cm 63" x 29" x 53"
Total Weight Without battery	149kg / 328lb 111kg / 244lb
Propulsion motor	950W / 1.26hp
Battery	12V 70Ah x 2
Charger	24V 8A
Controller	Dynamic Rhino II 120A
Front Suspension	2x shock absorber
Rear Suspension	1x shock absorber
Front Tyre	100/55-10 x 2 (14" / 36cm diameter)
Rear Tyre	100/50-10 x 2 14" / 36cm diameter)
Anti-tip Wheel	2.75" / 7cm diameter
Top Speed (Forward)	12.8kph / 8.0mph
Climbing angle	10°
Cruising range (see note)	40km / 25 miles
Min. turning radius	132cm / 51"
Ground clearance	100mm (3.9")
Kerb climbing ability	100mm (3.9")
Obstacle climbing ability	100mm (3.9")
Max. load weight (including goods)	182kg / 28 stone

Remark:

Drive Medical reserves the right to modify the specification if necessary. The final specification is subject to the individual scooter you purchase from your dealer.

Note:

The maximum driving distance is based on an ambient temperature of 20°C, a 100kg driver, a fully charged battery and a constant driving speed at 12.8kph/h with 70% battery power discharged. The surface is flat and even.

10 VIN NUMBER

To ensure the correct after sales service and warranty service support, please write down the scooter serial number. The serial number is located on the back right-hand side of the frame.

VIN Number	
Motor S/No.	
Controller S/No.	

Also, note your Drive Medical dealer below:

Dealer	
Address	
Postcode	
Telephone	

11 WARRANTY

There is a comprehensive twelve-month warranty from the date on which your new scooter is delivered. The warranty covers the scooter for repairs or replacement during this period. For more detail, please see the Warranty Conditions below.

Warranty Conditions:

1. Any work or replacement part installation must be carried out by an authorized Drive Medical dealer / service agent.
2. To apply the warranty should your scooter require attention please contact the designated service agent listed above.

3. Should any part of the scooter require repair or full or part replacement, as a result of a manufacturing or material defect within twelve months of receiving the scooter, replacement parts will be supplied free of charge.

Note: This guarantee is not transferable

4. Any repaired or replaced parts will be covered by this warranty for the balance of the warranty period on the scooter.
5. Consumable items supplied will not generally be covered during the normal warranty period unless such items require repair or replacement clearly as a direct result of a manufacturing or material defect.

Such items include (among others):
upholstery, tyres and batteries.

6. The above warranty conditions apply to brand new scooter purchased at the full retail price. If you are unsure whether your scooter is covered, check with the service agent.
7. Under normal circumstances, no responsibility will be accepted where the scooter has failed as a direct result of:
 - a) The scooter or part not having been maintained in accordance with the manufacturer's recommendations.
 - b) Failure to use the manufacturer's specified parts
 - c) The scooter or part having been damaged due to neglect, accident or improper use
 - d) The scooter or part having been altered from the manufacturer's specifications or repairs having been attempted before the service agent is notified

Please note your local service agent's contact details in the previous box. In the event of your scooter requiring attention, contact them and give all relevant details so they can act quickly.

The manufacturer reserves the right to alter without notice any weights, measurements or other technical data shown in this manual. All figures, measurements and capacities shown in this manual are approximate and do not constitute specifications.

Appendix A: Service Record

YEAR	1	2	3	4	5	YEAR	1	2	3	4	5
Service Dates						Service Dates					
Controller						Upholstery					
On/off switch						Seat					
Control Lever						Back					
Braking						Armrests					
Recharge point						Electrics					
Batteries						Connections condition					
Levels						Lights					
Connections						Test run					
Discharge test						Forwards					
Wheels and Tyres						Reverse					
Wear						Emergency stop					
Pressure						Left turn					
Bearings						Right turn					
Wheel nuts						Slope test					
Motors						Over obstacles					
Wiring						List Items repaired					
Noise											
Connections											
Brake											
Brushes											
Chassis											
Condition											
Steering											