



Gem CEILING LIGHT INSTALLATION GUIDE



WEARING GLOVES
IS RECOMMENDED

DANGER: ELECTRIC SHOCK RISK. FOR YOUR SAFETY,
TURN OFF ELECTRICAL POWER BEFORE BEGINNING
INSTALLATION AND USE CAUTION WHEN INSTALLING.

+1 888.399.9905

www.vault-light.com | sales@vault-light.com



VAULT GEM DOWN LIGHT Installation And Wiring Instruction

Installation Instruction:

Step 1. Carefully unpack fixture and all components.

Step 2. Disconnect power at main electrical panel before installation.

Step 3. Connect the fixture ground wire to the supply circuit ground wire using a wire nut(3 PCS).

Connect supply circuit ground wire to the mounting plate with GREEN hex-head ground screw.

Step 4. Twist the stripped fixture wire ends and connect with circuit wires (from J-box) together:

black to black(Live wire), and white to white(neutral wire). Twist together with the wire nuts

provided, ensuring that the conductors are no longer exposed.

Step 5. Attaching the fixture canopy to the J-Box by 2 screws provided.

Step 6. Attaching the opal glass shade to the canopy carefully .

Warning:

Do not touch bulb when the fixture is turned on,

Turn off fixture and allow to cold before replacing lamp.

Please use a qualified electrician to install this fixture.

