

## **ARMSTRONG VIVERO GOOD MAINTENANCE**

### **Initial Floor Care:**

1. Remove any dried adhesive residue with a clean white cloth dampened with low odor mineral spirits, carefully following warnings on container.
2. Sweep, dust mop or vacuum thoroughly to remove all loose dust, dirt, grit and debris.
3. Floors installed with adhesive should not be washed for the first four days after installation. This prevents excessive moisture from interfering with the adhesive bond and/or seam treatments. All other floors can be damp mopped immediately, using Armstrong Once 'n Done Resilient & Ceramic Floor Cleaner.
4. Floors installed with grouted seams: After the grout joints have dried and hardened, a very light application of properly diluted Armstrong Once'n Done Resilient & Ceramic Floor Cleaner and a white 3M pad may be used to remove the slight haze of grout residue that remains. Again, two buckets of clear, cool water should be used. Pick up residue with a clean damp sponge. Use the second bucket and sponge for a final rinse and cleanup. Buff dry with a soft cloth.

### **DAILY/ REGULAR MAINTENANCE:**

1. Sweep, dust mop or vacuum thoroughly to remove all loose dust, dirt, grit and debris. Clean walk off mats frequently.
2. Wash your floor regularly with properly diluted Once 'n Done Resilient and Ceramic Floor Cleaner concentrate or ready to use Once 'n Done Resilient and Ceramic Floor Cleaner trigger spray.
3. Vinyl flooring like other types of smooth floors may become slippery when wet. Allow time for floor to dry after washing.
4. Immediately wipe up wet areas from spills, foreign substances, or wet feet.

### **PERIODIC MAINTENANCE:**

1. For heavy duty cleaning use Armstrong New Beginning Deep Cleaning Floor Stripper as recommended on bottle, to remove dirt and residues that may be ground into the floor.
2. If the shine on your floor begins to dull, Armstrong has two products that will help rejuvenate the luster.
3. Armstrong Satinkeeper Resilient Low Gloss Floor Finish for low gloss floors and the Armstrong Shinekeeper Resilient Floor Finish for medium to high gloss floors.
4. Armstrong New Beginning may also be used to remove Armstrong Satinkeeper Resilient Low Gloss Floor Finish or Armstrong Shinekeeper Resilient Floor Finish.