



## ▶▶ BAGAR® AIRLISS G

### GENERAL INFORMATION

#### DESCRIPTION

- Ready-to-use spray-applied leveller
- Special airless formulation

#### INTENDED USE


- Internal walls and ceilings
- For preparing substrates before decoration (light-weight wall coverings, matt or satin gloss finish paints)

### PRODUCT ADVANTAGES

- ✓ Approximately 4 times quicker to apply than conventional traditional gypsum plaster
- ✓ Very easy to apply
- ✓ Easy to sand
- ✓ Very white
- ✓ Multipurpose : suitable for manual or mechanical application (airless or spray pump machine)
- ✓ Can be tinted upon request with water base colorants during the production process



**BAGAR**  
TECHNIQUE





# BAGAR<sup>®</sup>

## TECHNIQUE



This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: February 2015

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information cannot replace an appropriate description regarding the type and condition of the substrate. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that an updated edition of this sheet has not been issued.



## TECHNICAL DATA

▶ <b>PRESENTATION</b>	Ready-mixed water-based spray-applied leveller
▶ <b>COMPONENTS</b>	Acrylic resin emulsion and cellulose derivatives Selected inorganic fillers
▶ <b>DENSITY</b>	1,7 +/- 0,1
▶ <b>pH</b>	8,5 +/- 1
▶ <b>COLOUR</b>	White
▶ <b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
▶ <b>CLASSIFICATION</b>	NF T 36-005 - Family III, Class 2
▶ <b>NORM</b>	NF EN 165 66
▶ <b>VOC</b>	EU limit value for this product (cat.A/a) : 30 g - This product contains max 25 g/l VOC
▶ <b>FIRE CLASS</b>	EUROCLASS - A2 - S1,d0 Certificate available on request
▶ <b>HEALTH AND SAFETY</b>	Safety data sheet available on request or from <a href="http://www.quickfds.com">www.quickfds.com</a>
▶ <b>PACKAGING</b>	25 kg plastic bag with handle or 25 kg plastic bucket
▶ <b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C) and moisture

## USE

▶ <b>PREPARATION</b>	Mix before use
▶ <b>DILUTION</b>	Up to 3% if necessary
▶ <b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• <i>Equipment</i></li> </ul> Airless sprayer (min. output 5 litres/min) with 0.027" to 0.033" tips and an angle of 50° or 60° Refer to the machine operating instructions and to the spayer manufacturer's recommendations regarding use (pressure, tips) Neither strainer nor filter needed for application Spray pump machine (nozzles 5-6 mm) Trowel
• <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +30°C, or at a relative humidity of above 65% HR (hygrometry rate)
• <i>Equipment cleaning</i>	With water before completely dry
▶ <b>MAXIMUM APPLICATION THICKNESS</b>	5 mm per layer
▶ <b>AVERAGE CONSUMPTION</b>	From 0.8 to 1.5 kg/sqm depending on substrate roughness and the desired finish
▶ <b>SUBSTRATES</b>	Concrete, cellular concrete, brick, concrete block, cement, plaster, plasterboard, old paint substrates, glass cloth, old sprinkle effect Substrates must be hard, cohesive, clean, sound and dry
▶ <b>OVERCOAT</b>	BAGAR <sup>®</sup> levellers, light-weight wall coverings, matt or satin gloss paint