

Datasheet

ELKo Assortment 500 pcs.

Includes the most common aluminum electrolytic capacitors with 24 different values



Datasheet ElKo-Set

Component in circuit diagram:



The AZ-Delivery ElKo-Set consists of a reasonable combination of 24 different values from 0.1 μ F to 1000 μ F and thus allows comfortable working with breadboards and for experimental circuits.

Note: When using the components, be sure to observe the **correct polarity!**

Anode = no lateral marking, long wiring, VCC, "+pin"

Kathode= white marking strip short wiring, GND, ground "-pin".

Tolerance: to 20%

Temperature range: -40°C to +105°C

Position	Capacity	Rated voltage	Scope of delivery	Size, DxL
1	0.1uF	50V	30	4x7mm
2	10uF	50V	20	5x11mm
3	100uF	25V	15	5x11mm
4	0.22uF	50V	20	5x11mm
5	22uF	16V	30	4x7mm
6	220uF	10V	15	5x11mm
7	0.47uF	50V	20	5x11mm
8	22uF	25V	30	4x7mm
9	220uF	25V	15	8x12mm
10	1uF	50V	20	6x11
11	33uF	16V	30	4x7mm
21	330uF	25V	10	8x12mm
13	2.2uF	50V	30	4x7mm
41	47uF	10V	30	4x5mm
15	470uF	10V	10	6x11mm
16	3.3uF	50V	30	4x7mm
17	47uF	25V	20	5x11mm
18	470uF	16V	10	8x12mm
19	4.7uF	50V	30	4x7mm
20	47uF	50V	15	6x11mm
21	680uF	16V	10	8x12mm
22	10uF	25V	30	4x7mm
23	100uF	16V	20	5x11mm
24	1000uF	16V	10	8x16mm