

Enjoy this hybrid version of a traditional style. The UC480MLA was designed as combination medium/large size recliner that fits individuals of different heights. The plush, biscuit-back design and luxurious chaise pad makes this everyone's favorite seat in the house.



Positioning you for life.



UC480MLA

*Additional upcharge



UC480

Model Number	UC480
Size	Medium/Large
Weight Capacity	375 LB
Recline Positions	3
Chaise Seat	Yes
Pocketed Coil Seating System	No
Back Type	Biscuit
Head Rest Cover	Yes
Arm Covers	Yes
Battery Back Up	Yes
Overall Width	35"
Overall Height	41.5"
Width Between Arms	22"
Floor to Top of Seat	22"
Seat Depth	22"
Seat to Top of Back	31"
Seat to Top of Arm	7"
Seat Angle Raised	20°
Distance Required from Wall Reclined	19"
Extension Reclined from Back of Seat to End of Foot Rest	44"
Life Time Warranty, Chair Frame, Lift Frame, Recline Frame, Recline Mechanism	Yes
Warranty on Electrical parts	3 YR
Pro Rated Years 4 Thru 7	Yes
Warranty on Mechanical Labor	3 YR
Warranty on Electrical Labor	1 YR
Warranty on Fabric and Foam, and Pocketed Coils	1 YR
Removable Back Option	Yes
Left Hand Control Option Available	Yes
Extra Pocket Option Available	Yes
4-Motor Heat & Massage Available	No
2-Motor Heat & Massage Available	Yes
Foot Rest Extension Option Available	Yes
Smart Tek Standard	Yes

* See Customize Chart for dimension limits

Sizes may vary depending on fabric, filling material, upholstery and carpet thickness. All measurements taken on concrete floor using levels and metal rulers.



User-friendly feature of every UltraComfort lift and recline chair:

Easy to use battery backup system. Each UltraComfort lift and recliner has a battery backup system in the electrical transformer which operates on two 9 volt batteries. In the event of a power failure, the battery system will raise the chair from the reclined to the seated position. The batteries should be replaced after one use.





Positioning you for life.

UltraComfort Phone: 866-793-5100 Fax: 866-255-9962 web: www.ultracomfort.net





Complies with UL 73 and CSA C22.2 No. 68

SHT-UC480MLA-043018