

Z-Drag Guide



1. Find a suitable anchor for the **BLUE** side.
2. Attach the **GREEN** side to the recovery object. (Forks, Frame, etc)
3. Pull the **GREEN KNOT**. Pulling towards the **BLUE** end is more powerful.
4. To adjust length release the cam holding the recovery object.
5. To adjust pull slack release the cam holding the **GREEN KNOT**.
6. To reset the Z-Drag release the cams on the **ORANGE** part and walk away from the anchor while holding down the tabs.
7. After resetting, attach the recovery object side to the bag. Then stuff the webbing into the bag working your way back to the anchor side. This will prevent tangling and have it ready to deploy next time.

Z-Drag Safety

1. **NEVER** exceed the 1000 lb working load of the Z Drag system.
2. **NEVER** stand in the path, downhill, or below your recovery object.
3. **ALWAYS** inspect your Z-Drag for any signs of wear or damage.
4. **NEVER** use the Z-Drag if it shows signs of wear or damage.
5. **NEVER** use the Z-Drag for climbing or to support life.
6. **NEVER** use the Z-Drag for anything other than its intended purpose.

Dead Man Anchor Option

If no anchor is available, fill the bag with dirt and rocks. Dig a small hole with a channel for the webbing. Attach the **BLUE** end around the bag and bury. You can also wedge the bag in a rock crevice or between suitable objects.