



# BJÖRK Warm-Air Hand Dryer 110-120 V 3010/3012/3016



reddot award  
winner

**High-speed  
IR-sensor and electronic timer  
5-year warranty**



DAN DRYER BJÖRK high-speed hand dryer in award-winning design, featuring unbroken lines and a slender, almost weightless look in modern Scandinavian design. The hand dryer is equipped with top plate in six available colors.

### Application

DAN DRYER BJÖRK is a powerful machine with high air velocity and therefore best suited for places with some tolerance of noise. The elegant design line is suitable for all types of public toilets.

### Technical data

	BJÖRK Prod. No.: 3010, 3012, 3016 Touch-free warm-air hand dryer with IR sensor
Type	
Dimensions	H:12.99" x W:8.07" x D:7.21"
Material	Powder coated stainless steel
Drying cycle	10-15 sec.
Connection	110-120 V, 50/60 Hz, Class I
Total wattage	1600 W
Heating element	450-900 W
Motor	350-700 W
Noise level	76 dBA
Max. air capacity	246'-328'/sec.
Max. Air outlet temperature	140° F
Net weight	12.57 lb
IP rating	IPX1

### Tender text

Touch-free hand dryer equipped with top plate. Powder coated stainless steel housing. Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IPX1, 110-120 V, 50/60 Hz, 1600 W, Class I (earthed). 76 dBA. Net weight: 12.57 lb. H:12.99" x W:8.07" x D:7.21".


Approval  
UL - CUL



RoHS  
Compliant



Negro Ingo 3070



Bianco Male 3072



Birch 3076



Eastwood Lava 3081



Naturel Concrete 3082



Slate 3083

### References

Offices and administration, shopping malls, restaurants, hotels, airports and public swimming pools, schools, public institutions and cultural centres.

### Standard color

Prod. No. 3010: RAL 9003, white, gloss 60.  
Prod. No. 3012: RAL Classic colors.  
Prod. No. 3016: RAL 9005, matte black, gloss 10.

### Top plate

The self-adhesive laminate top plate is available in six optional standard colors.

### Activation

Infrared sensor and electronic timer. Touch-free. Activation distance adjustable between 2"-13". Automatic stop after 60 seconds of continuous use.

### Motor type

Commutator motor with carbon brushes. 12,000-18,000 revolutions/min.

### Protection

Automatic thermal cut-out in both motor and heating element.

### Installation

Machine intended for wall-mounting and fixed installation via circuit-breaker. Installation must be carried out by a qualified electrician.