LOKI dispenser 4040/4042/4044/4046, 4050/4052/4054/4056, 4060/4062/4064/4066

Manual operation For liquid soap, foam soap or disinfectant 2-year warranty



LOKI manual dispensers are part of DAN DRYER's newest line of sanitary equipment. The product line is characterised by elegant lines and the "I" on the front, which ties together the line and creates harmony when multiple LOKI products are displayed side by side.

Application

The LOKI line has been created to complement surrounding interior architecture such as window, doors, and wall surfaces. The elegant design and the floating look make the products easily integratable in most commercial and public washrooms.

Technical data	
	LOKI
	Prod. No.: 4040/4042/4044/4046,
	4050/4052/4054/4056,
	4060/4062/4064/4066
	Manual dispenser for liquid soap/foam
Type	soap/disinfectant
Dimensions	H 328 x W 131 x D 115 mm
Material	Brushed/powder coated stainless steel
Capacity	0.61
Net weight	2.7 kg

Tender text

Manually operated dispensers for liquid, gel and foaming soap/disinfectant. Brushed/powder coated stainless steel housing. Capacity: 0.6 l. Net weight: 2.7 kg. H: 328 mm, W: 131 mm, D: 115 mm.

References

Offices and administration, shopping malls, restaurants, hotels, airports, sports facilities and public swimming pools, schools, public institutions and cultural centres.

Prod. No.: 4040/4042/4044/4046: For liquid soap and gel disinfectant.

Prod. No.: 4050/4052/4054/4056: For liquid disinfectant.

Prod. No.: 4060/4062/4064/4066: For foaming

soap and disinfectant.

Standard colours

Prod. No. 4040/4050/4060: Brushed stainless steel.

Prod. No. 4042/4052/4062: RAL 9003, white, gloss 60.

Prod. No. 4044/4054/4064: RAL 9005, matt black, gloss 10

Prod. No. 4046/4056/4066: RAL Classic colours

Activation

Manual operation. Press the dosage lever slightly backwards for dosage. Dosage stops as soon as pressure is released. Access to the internals of the dispenser is only possible with a special key fitting all LOKI products.

Installation

Wall mounting.