

Instruction Manual





For more information, please feel free to contact our Head Office on 021 300 1137 or info@noola.co.za

www.noola.co.za

Contents

Warranty	01
What's in your box?	02
How to install the brake system and wheels	03
How to open and close your frame	04
How to attach car seat onto your frame	05
How to change bassinet/carrycot to toddler seat	06-07
How to adjust handle and seat position	08
How to correctly use the brake system	09
Fabric and stroller care	10
Warning	11

LIMITED WARRANTY

Congratulations!! By purchasing your Nula you've increased the fun and excitement that you and your family will have.

This Nula product is warranted from the date of delivery against defects in material or workmanship as follows: fabric parts for 6 months, frame and plastic parts for 12 months.

Your original dated sales invoice is your proof of purchase.

The warranty will start upon delivery/collection of your product.

If a defect in material or workmanship is discovered during the Limited Warranty period, Nula will repair or replace your product at no cost to you.

This warranty is only valid in the country in which the product was purchased.

The Limited Warranty extends only to the original purchaser of this product and is not transferable to anyone who obtains ownership of the product thereafter.

The Limited Warranty does not cover claims resulting from misuse,

failure to follow instructions, installation, improper maintenance, general wear and tear, worn wheels, worn/torn fabric, abuse, alteration, in an accident and normal wear and tear.

If you are not happy with the product and wish to return it, this can be done within 7 days provided that it has not been used,

returned in the same packaging and is in a resalable condition.

The cost to return the item to our warehouse is for the clients account.

Refunds will be processed within 10 working days once we have received the item and the above criteria has been met.

The Limited Warranty does not cover products which are used in rental operations and NulaBaby will not be held liable for any incidents or commercial damages relating to such use.

For warranty service or replacement part information, please contact NulaBaby directly by emailing product@nulababy.co.za

Please be prepared to provide the product model, photographs and a description of the warranty issue. Some replacement parts may be available for purchase after this limited warranty expires.

Please visit us at www.nulababy.co.za for more information.

We wish you many happy kilometres with your new Nula.

Love Always TeamNula

What's in your box?



A: BASSINET/TODDLER SEAT HOOD

B: STROLLER HANDLE

C: ADJUSTABLE BUTTON FOR HANDLE HEIGHT

D: FOLDING MECHANSIMS

E: BASSINET/TODDLER SEAT HANDLE BAR

F: SEAT ADJUSTMENT BUTTONS

G: POCKETS

H: BASSINET/TODDLER FRAME

I: BASKET

J: REAR WHEEL

K: BRAKE SYSTEM

L: LOCK FOR FRONT WHEEL (ANTI-SWIVEL)

M: FRONT WHEEL

How to install the brake system and wheels



Align brake system as indicated in photograph 1, and connect.

Once you hear the click on either side, the brake system is securely attached.



Attach rear wheels on either side of brake system. as seen in photograph 3.



You will hear a click, this indicates they are attached.



Attached the front wheels by placing the steel pin into the machansim as shown in photograph 4.

How to open and close your frame

How to install car seat onto your frame



TO OPEN:

Release saftey mechanism on the right-hand side of the frame. Place both hands on either side of frame and open.



TO CLOSE:

Pull both mechanism while pushing the button on the right-hand side. (Refer to page. 2 letter marked 'D') Please note: there is only a button on the right-hand side.



Once you have pulled these mechansims, push the frame down and it will close. The saftey catch will lock stroller.





Insert car seat adapters into the car seat base on either side. You will hear a click once inserted.

This will remain in the car seat at all times and you will NOT need to remove and re-insert.



Align car seat to stroller frame and push down.

Once hearing a click, you are now rest assured your car seat is securely attached.



Car seat is attached, as seen in photograph 3.

04

How to change bassinet/carrycot to toddler seat



WHEN SHOULD WE CHANGE FROM BASSINET TO TODDLER SEAT?

Your baby is ready to move once he/she starts pulling him/herself up and wants to sit.

The toddler seat can be used from 9kg and not newborn.




You would've received the bassinet already assembled in your box as shown in photograph 1.



Remove mattress and hard board from bassinet.

Release velcro strips. There are two on the top of the frame.





Slip the material from the frame as shown in photograph 3, until you end up with the naked frame, shown in photograph 4.

How to change bassinet/carrycot to toddler seat



You will notice two pins on either side of the frame. This indicates, the bottom half of the frame.

Slip the fabric part of the toddler seat over the top part of the frame.



Connect the velcro strips on the bottom of the frame.



Place the silver ring over the pin on both sides and connect the clip at the back of the frame as shown in photograph 8.



06

How to adjust the handle and seat position

Press both buttons on either side to adjust the hndle height and release.






Press both 'tilt' buttons on either side simontanousely to recline the seat.

The seat can adjust to a 45°, 60° and 75° for the perfect position ensuring your baby is comfotable.





How to correctly use the brake system



It is **recommended** to use the brake system in a locked position before placing your any attachement onto the frame.



Press button down marked as 'A' in photograph 2 to lock the front wheel. Once the wheel is in position it will lock automatically. To unlock, push the button upwards.

Fabric and stroller care

STROLLER CARE

Clean the plastic components with a dmap cloth. DO NOT USE harsh chemicals like bleach.

In very dry climate areas, clean and lubricate the wheels, saftey locks and sliding parts with light oil or silicon spray. DO NOT USE heavy oils as this will attract dust and dirt and will lead to clog and damage parts.

FABRIC CARE

Fabric is splash resistant. In the event your stroller becomes wet, leave to dry in a shaded area and NOT in direct sunlight.

Washing instructions: Wipe clean only.

Light soiling to the fabric can be removed with a damp cloth/sponge and light detergent. DO NOT USE harsh chemicals.

WARNING

Read this instruction manual carefully.

The maximum weight allowance for the car seat is 13kg.

To avoid the risk of suffocation, keep all plastic packaging and materials out of reach of children.

You are personally responsible for the saftey of your baby at all times.

Always set the parking break on the stroller. Never leave child unattended.

Always secure your child in the saftey harness at all times.

Regularly check that the saftey harness is correctly fitted and that the webbing has not become frayed or damaged.