


NLS-FM430

Fixed Mount Barcode Scanner



Features

IR/Light Triggers

The combination of IR sensor and light sensor exhibits an improved sensitivity in activating the scanner to scan barcodes as they are presented, to achieve higher throughput and productivity.

Automatic Exposure Control (AEC)

The sensor in the NLS-FM430 automatically adjusts the supplementary lighting duration based on the light reflected off barcode.

IP54-sealed Housing

The NLS-FM430 is environmentally sealed to an IP54 rating to prevent dust, moisture and other contaminant from entering it.

Unmatched Reading Performance

Armed with Newland's fifth-generation of **UIMG®** technology, the NLS-FM430 is capable of reading 1D as well as high-volume 2D barcodes on the screen covered with protective film.

Highly Visible Laser Aimer

The NLS-FM430 provides a laser-generated crosshair aiming pattern that is clear and bright even in bright sunlight, ensuring first time accurate aim.

1.5m Drop Resistance

The scanner withstands multiple 1.5m drops to concrete (for six sides, three drops per side).

Application Scenarios

Self-service cabinets used in e-commerce, express delivery services and smart homes; ticket validators; kiosks; barrier gates; O2O applications.

NLS-FM430

SCANNING MADE SIMPLE

Fixed Mount Barcode Scanner

Performance	Image Sensor	1280 * 800 CMOS		
	Illumination	White LED		
	Aiming	Laser diode or green LED		
	Symbolologies	2D	PDF417, QR Code, Data Matrix, AZTEC, CSC, Maxicode, Micro QR, Micro PDF417, GM, Code One, etc.	
		1D	EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 39, Codabar, UCC/EAN 128, RSS, ITF, ITF-14, ITF6, Standard 25, Matrix 25, COOP 25, Industrial 25, Plessey, MSI Plessey, Code 11, Code 93, Code 49, Code 16K, etc.	
	Resolution*	≥3mil		
	Typical Depth of Field*	EAN-13	55-360mm (13mil)	
		Code 39	70-180mm (5mil)	
		PDF417	55-160mm (6.7mil)	
		Data Matrix	50-170mm (10mil)	
		QR Code	40-210mm (15mil)	
	Scan Mode	Sense mode, Continuous mode, Level mode, Pulse mode		
	Scan Angle**	Roll: 360°, Pitch: ±55°, Skew:±55°		
	Field of View	Horizontal 51°, Vertical 32°		
	Min. Symbol Contrast*	25%		
Mechanical/ Electric	Interface	RS-232, USB		
	Dimensions	41.5(W)×49.5(D)×24.3(H)mm		
	Weight	75g		
	Notification	Beep, LED indicator		
	Rated Power Consumption	1622mW (typical)		
	Operating Voltage	5VDC±5%		
	Current @ 5VDC	Operating	276.8mA (typical), 322.7mA (max.)	
		Standby	83.3mA	
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)		
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)		
	Humidity	5% to 95% (non-condensing)		
	ESD	±14 kV (air discharge), ±8 kV (direct discharge)		
	Drop	1.5m		
	Sealing	IP54		
Certifications	FCC Part15 Class B, CE EMC Class B, RoHS, IEC60825, IEC62471, KC			
Environmental	Cable	USB	Used to connect the NLS-FM430 to a host device.	
		RS-232	Used to connect the NLS-FM430 to a host device.	
	Power Adapter	DC5V adapter to power the NLS-FM430 with RS-232 cable.		

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR Code:10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V1.1

Newland China
+86-591-83978605
contact@nlsan.com
www.newlandaidc.com

Newland Europe
+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America
+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America
+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan
+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea
+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com