

# BRIGHTSIGN HD

AN UPDATED CLASSIC NOW WITH TRUE 4K. MAINSTREAM PERFORMANCE.

BrightSign HD models are ideal for mainstream 4Kp60, Full HD and HTML5 applications that require high reliability and ease of use. All models offer H.265 decoding, HTML5 rendering and Gigabit Ethernet. Robust interactive controls, live content features, Video Walls and Mosaic Mode make this set of players a perfect fit for a wide range of applications.



## BrightSign HD224

### Standard I/O Player

Enjoy flawless 4K and Full HD single video decoding, mainstream HTML5 performance and simultaneous playback from local, networked and streaming sources. Includes the standard I/O package of Gigabit Ethernet, GPIO, and analog/digital audio.











## BrightSign HD1024

### Expanded I/O Player

All the features of the HD224 plus additional interactive options via USB 2.0 (type A), and serial ports to fully engage your audience.

## Features

- |  |   |  |  |  |  |  |  |
|--|---|--|--|--|--|--|--|
| <br>4K60p single decode | <br>Mainstream HTML5 | <br>1080p60 single decode | <br>H.265           | <br>HDR10 & HLG | <br>Mosaic Mode | <br>Entry-Level HTML5 | <br>Digital Audio |
| <br>IP Streaming        | <br>BrightBeacon™    | <br>Video Walls           | <br>AutoWall™       | <br>Zones       | <br>Interactive | <br>Live Feeds        | <br>Geo-Fencing   |
| <br>Sign Preview        | <br>Tagging          | <br>BrightSign App        | <br>Remote Snapshot | <br>Networking  | <br>B-Deploy    |  |  |

## SPECIFICATIONS

MODEL	HD224	HD1024
<b>VIDEO ENGINE DECODER</b>		
True 4K@60p video decoding	X	X
Single 4K or 1080p60 video decoding	X	X
<b>MEDIA FORMATS</b>		
Video Codecs for 4K content: H.265/H.264	X	X
Video Containers for 4K H.265/H.264 content: .ts, .mov, .mp4	X	X
Video Codecs for Full HD: H.265, H.264(MPEG-4, Part 10), MPEG-2, MPEG-1	X	X
Video Containers for Full HD: .ts, .mpg, .vob, .mov, .mp4, .m2ts	X	X
Images: BMP, JPEG, PNG	X	X
Audio: MP2, MP3, AAC, and WAV (AC3 is passed through)	X	X
HTML5	X (Mainstream)	
<b>DISPLAY RESOLUTIONS</b>		
4K resolutions: 4096x2160, 3840x2160, 3840x600	X	X
Upscaling to: 3840x2160x24/25/29.97/30p	X	X
1920x1200, 1920x1080x24/25/29.97/30/50/59.94/60p, 1920x1080x50/59.94/60i, 1600x1200x60p, 1440x1050x60/75p, 1440x900x60/75p, 1360x768x60p, 1280x1024x60/75p, 1280x960x60p, 1280x800x60p/75p, 1280x768x60p, 1280x720x50/59.94/60p, 1024x768x60p, 800x600x60/75p, 720x576x50p/50i, 720x480x59.94/60p/60i, 640x480x60p	X	X
<b>HARDWARE INTERFACES</b>		
External micro SD Slot (SDHC and SDXC); SDHC storage up to 32GB SDXC storage up to 2TB	X	X
USB High Speed Host Port (also supports content updates)		X (Type A)
12-pin Phoenix GPIO port with 8 bi-directional GPIOs	X	X
3.5mm RS-232 Serial Port		X
3.5mm IR In/Out	X	X
3.5mm Audio Out (analog -or- SPDIF digital, non-simultaneous)	X	X
HDMI 2.0a Out	X	X
Ethernet	X (Gigabit)	
M.2 (E) Keyed Wi-Fi/Bluetooth Connector	X	X
Wi-Fi External Antenna Connector (optional)	X	X
Status LEDs	Power, Error, Busy, Update	
Reset and Service Buttons	X	X
Real Time Clock	X	X
<b>FEATURES</b>		
H.265 Decoding: smaller file sizes and lower bitrates than H.264	X	X
HDR10 & HLG	X	X
HTML5: hardware-accelerated engine that plays modular HTML assets flawlessly alongside high-bandwidth video	X (Mainstream)	
BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage (requires: wireless/Bluetooth module)	X	X

MODEL	HD224	HD1024
Video Walls: synchronized playback across multiple displays	X	X
AutoWall™: embraces the power of HTML5 to create unique multimedia video walls	X	X
Zones: playback multiple content types on a single screen	X	X
Mosaic Mode: simultaneously play a multitude of smaller resolution videos that add up to the maximum video resolution of the player	X	X
IP Streaming: play streaming media	X	X
Interactivity: connect virtually any type of interactive device to a multitude of interactive ports	X (GPIO, UDP)	X (GPIO, USB, serial, UDP)
Live Feeds: Live Data, Live Text, MRSS, Twitter, Flickr, etc.	X	X
Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution	X	X
BrightSign App: update signs with an iOS device	X	X
Geo-Fencing: trigger playback based on location (requires USB dongle)		X
Sign Preview: preview presentation playback in BrightAuthor	X	X
Remote Snapshot: remotely view a snapshot image of the display's playback	X	X
Networking: update, manage and schedule your signage	X	X
B-deploy: A setup feature to deploy many players at once	X	X
Extended Thermal: sustained ambient temperatures between -20°C and 50°C with transients up to 70°C at 90% max relative humidity, non-condensing	X	X
<b>SOFTWARE</b>		
Free BrightAuthor Software	X	X
BrightSign Networking Options	X	X
<b>ACCESSORIES</b>		
USB Button Pads		X
Wireless/Bluetooth Module	X	X
MicroSD Class 10 Cards (various capacities)	X	X
<b>MISCELLANEOUS</b>		
Dimensions (W x H x D)	159.9 x 22 x 144.2mm or 6.3 x 0.87 x 5.7 in	
Weight	12 oz	
Power	12V / 1.5A (18 Watts)	
Multi-Country Power & Regulatory Approvals	X	X
Built-in Wall Mounting Brackets	X	X
1 year warranty, parts and labor*	X	X

\*2 year warranty, parts and labor, for units shipped from an EU or UK distribution center and to an EU or UK address.