

NLS-FR80

Desktop Barcode Scanner



Features

■ Superior Scanning Performance

Armed with Newland's sixth-generation of **UIMG[®]** technology, this scanner can scan 1D and 2D barcodes and delivers stunning performance on decoding the EAN-13 barcode.

■ High Motion Tolerance

With 3.5m/s motion tolerance, the scanner can quickly capture moving goods, which greatly enhances efficiency.

■ Multiple Status indicators

6 kinds of status indicators show current working status of the scanner, including decoding, configuration, communication and abnormal status.

■ Advanced Sense Mode

The scanner activates a decode session every time it detects a barcode presented to it, and the target barcode shown in the window will not be read repeatedly.

■ Sound Effect & Volume keys

Sound effect and volume keys are provided for users to select one suitable for their application environment.

■ Large Scan Window

Large scan window meets demands of goods with different sizes. When goods comes closer to the scan window, the scanner will conduct quick scanning.

Application Scenarios (as an accessory)

Self-service retail devices, supermarkets, etc.

NLS-FR80

SCANNING MADE SIMPLE

Desktop Barcode Scanner

Performance	Image Sensor	1280 * 1088 CMOS		
	Illumination	Red LED (614nm~624nm)		
	Symbolologies	2D	PDF417, QR Code, Data Matrix, Aztec	
		1D	Code11, Code128, Code39, Code32 (Italian Pharma Code), GS1-128 (UCC/EAN-128), AIM 128, ISBT 128, CodaBar, Code 93, UPC-A/UPC-E, Coupon, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2/5, Matrix 2/5, Industrial 2/5, ITF-14, ITF-6, Standard 2/5, China Post 25, MSI-Plessey, Plessey, GS1 Databar, Composite, GS1 Databar (RSS)	
	Resolution*	≥3mil (1D)		
	Typical Depth of Field*	EAN-13 (13mil): 0mm-140mm	EAN-13 (5mil): 50mm-90mm	
	Scan Mode	Advanced sense mode		
	Min. Symbol Contrast*	≥15% (Code 128 10mil)		
	Scan Angle**	Roll: 360°, Pitch: ±55°, Skew: ±50°		
	Motion Tolerance*	350cm/s		
	Field of View	Horizontal 42.4°, Vertical 36°		
Mechanical/	Interface	RS-232, USB		
Electrical	Operating Voltage	5 VDC±5%		
	Power Consumption	Operating	2W (typical), 2.5W (max)	
		Standby	1.25W	
	Dimensions	Without base: 151 (W)×141.5 (H) ×97.5 (D)mm		
		With base: 151 (W)×156.5 (H)×108.5 (D)mm		
	Weight	542g (without base), 678g (with base)		
	Notification	Beep, LED indicator		
Environmental	Operating Temperature	-20°C to 50°C		
	Storage Temperature	-40°C to 70°C		
	Humidity	5% to 95% (non-condensing)		
	ESD	±15 KV (air discharge); ±8 KV (direct discharge)		
	IP Level	52		
Certifications	FCC Part15 Class B, CE EMC Class B			
Accessories	Cable	USB	Used to connect the scanner to a host device.	
		Power Adapter	DC 5V power adapter to power the scanner.	

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version:V1.0

Newland China

+86-591-83978605
contact@nlsan.com
www.newlandaidc.com

Newland Europe

+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America

+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America

+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan

+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea

+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com

