



Aluminum Spiral Duct Mounted Grille Single or Double Deflection • Optional Damper/Extractor

Model: US301FL • Universal Endcaps • Single Deflection • Long Blades • 3/4" Blade Spacing US301FS • Universal Endcaps • Single Deflection • Short Blades • 3/4" Blade Spacing US300FL • Universal Endcaps • Double Deflection • Long Front Blades • 3/4" Blade Spacing US300FS • Universal Endcaps • Double Deflection • Short Front Blades • 3/4" Blade Spacing






Available Duct Diameter by Height

<u> </u>						
Height	3"	4"	6"	8"	10"	12"
Min : Max	10" : 36"	10" : 36"	12" : 36"	20" : 36"	24" : 36"	24" : 36"
Duct Diameter						

Typical Installation



Standard Finish: #26 White

Optional Extractor:

Model ASD - Air Scoop Device. Extractor must be ordered with grille. Cannot be field installed.

Application Notes:

For duct velocities up to 800 fpm, the extractor is not required. For duct velocities higher than 800 fpm, the extractor is recommended.

General Description

- Spiral Grilles save contractor installation time and money by directly mounting to the duct.
- Available with single or double deflection, with adjustable louvers vertical or horizontal.
- Front louvers available in vertical or horizontal.
- All-aluminum construction with universal end caps to match duct diameters from 10" thru 36" in even increments.
- Foam gasketing standard for tight seal to duct.
- Optional ASD (Air Scoop Device) operable with Phillips screwdriver for volume adjustment, accessible from grille face.