


PERFORMANCE DATA
diffusers
TMSA / SQUARE CEILING / ROUND NECK / HIGH PERFORMANCE / HORIZONTAL TO VERTICAL DISCHARGE

| | | Neck Velocity | 400 | 500 | 600 | 700 | 800 | 1000 | 1200 | 1400 | 1600 |
|-----------------------|----------|---------------------|------------|-------|-------|-------|-------|--------|--------|--------|--------|
| | | Velocity Pressure | 0.010 | 0.016 | 0.022 | 0.031 | 0.040 | 0.062 | 0.090 | 0.122 | 0.160 |
| 12" x 12" Module Size | 4" Dia. | Airflow, cfm | 35 | 44 | 52 | 61 | 70 | 87 | 105 | 122 | 140 |
| | | Total Pressure | Horizontal | 0.012 | 0.018 | 0.026 | 0.036 | 0.046 | 0.072 | 0.104 | 0.142 |
| | | Vertical | | 0.013 | 0.021 | 0.030 | 0.041 | 0.053 | 0.083 | 0.120 | 0.164 |
| | | Throw feet | Horizontal | 1-1-2 | 1-2-3 | 1-2-4 | 1-2-4 | 2-2-5 | 2-3-6 | 2-4-7 | 3-4-8 |
| | | Vertical | | 1-1-2 | 1-1-2 | 1-1-3 | 1-2-3 | 1-2-3 | 1-2-3 | 2-3-4 | 2-3-4 |
| | | NC (Noise Criteria) | Horizontal | - | - | - | - | 13 | 20 | 25 | 30 |
| | | Vertical | | - | - | - | - | - | 16 | 21 | 26 |
| | 5" Dia. | Airflow, cfm | 55 | 68 | 82 | 95 | 109 | 136 | 164 | 191 | 218 |
| | | Total Pressure | Horizontal | 0.018 | 0.028 | 0.041 | 0.056 | 0.073 | 0.114 | 0.164 | 0.223 |
| | | Vertical | | 0.022 | 0.034 | 0.049 | 0.066 | 0.086 | 0.135 | 0.194 | 0.265 |
| | | Throw feet | Horizontal | 1-2-3 | 1-2-4 | 2-2-5 | 2-3-5 | 2-3-6 | 3-4-8 | 3-5-9 | 4-5-10 |
| | 6" Dia. | Vertical | | 1-1-2 | 1-1-3 | 1-2-3 | 1-2-3 | 1-2-4 | 2-3-4 | 2-3-5 | 3-3-5 |
| | | NC (Noise Criteria) | Horizontal | - | - | - | 14 | 18 | 25 | 31 | 36 |
| | | Vertical | | - | - | - | 12 | 15 | 22 | 27 | 32 |
| | | Airflow, cfm | 78 | 98 | 118 | 137 | 157 | 196 | 235 | 274 | 314 |
| | 7" Dia. | Total Pressure | Horizontal | 0.026 | 0.041 | 0.059 | 0.080 | 0.105 | 0.164 | 0.236 | 0.321 |
| | | Vertical | | 0.032 | 0.049 | 0.071 | 0.097 | 0.126 | 0.198 | 0.284 | 0.387 |
| | | Throw feet | Horizontal | 1-2-4 | 2-2-5 | 2-3-6 | 2-3-7 | 2-4-7 | 3-5-9 | 4-6-11 | 4-7-12 |
| | | Vertical | | 1-1-3 | 1-2-3 | 1-2-4 | 2-2-4 | 2-3-4 | 2-3-5 | 3-4-5 | 3-4-6 |
| | 8" Dia. | NC (Noise Criteria) | Horizontal | - | - | 14 | 19 | 23 | 30 | 36 | 40 |
| | | Vertical | | - | - | 12 | 17 | 21 | 27 | 32 | 37 |
| | | Airflow, cfm | 107 | 134 | 160 | 187 | 214 | 267 | 320 | 374 | 427 |
| | | Total Pressure | Horizontal | 0.036 | 0.056 | 0.080 | 0.110 | 0.143 | 0.223 | 0.322 | 0.438 |
| | 9" Dia. | Vertical | | 0.044 | 0.068 | 0.098 | 0.133 | 0.174 | 0.272 | 0.392 | 0.533 |
| | | Throw feet | Horizontal | 1-2-4 | 2-3-5 | 2-3-7 | 3-4-8 | 3-4-9 | 4-5-11 | 4-7-13 | 5-8-14 |
| | | Vertical | | 1-2-3 | 1-2-4 | 2-2-4 | 2-3-5 | 2-3-5 | 3-4-6 | 3-4-6 | 4-5-7 |
| | | NC (Noise Criteria) | Horizontal | - | 12 | 18 | 23 | 27 | 34 | 40 | 49 |
| | 10" Dia. | Vertical | | - | - | 16 | 21 | 25 | 31 | 37 | 41 |
| | | Airflow, cfm | 140 | 175 | 209 | 244 | 279 | 349 | 419 | 489 | 558 |
| | | Total Pressure | Horizontal | 0.047 | 0.073 | 0.105 | 0.143 | 0.187 | 0.292 | 0.421 | 0.573 |
| | | Vertical | | 0.057 | 0.090 | 0.129 | 0.175 | 0.229 | 0.358 | 0.516 | 0.702 |
| | 11" Dia. | Throw feet | Horizontal | 2-2-5 | 2-3-6 | 2-4-7 | 3-4-9 | 3-5-10 | 4-6-12 | 5-7-14 | 6-9-16 |
| | | Vertical | | 1-2-4 | 1-2-4 | 2-3-5 | 2-3-6 | 2-4-6 | 3-4-7 | 4-5-7 | 4-6-8 |
| | | NC (Noise Criteria) | Horizontal | - | 16 | 22 | 26 | 31 | 37 | 43 | 48 |
| | | Vertical | | - | 15 | 20 | 25 | 29 | 35 | 41 | 45 |

- Data obtained from tests conducted in accordance with ANSI/ASHRAE Standard 70-2006. Actual performance, with flexible duct inlet, may vary in the field. See the Engineering Guidelines section of this catalog for additional information.
- If the diffuser is mounted on an exposed duct, the throw values are 70% of those listed in the table
- Throw values given are for terminal velocities of 150, 100 and 50 fpm and for isothermal conditions. See the section, Engineering Guidelines for the catalog throw data information.
- NC values are based on octave band 2 to 7 sound power levels minus a room absorption of 10 dB
- Each NC value represents the noise criteria curve that will not be exceeded by the sound pressure in any of the octave bands, 2 through 7, with a room absorption of 10 dB, re 10^{-12} watts
- Dash (-) in space denotes an NC value of less than 10
- All pressures are given in inches of water
- To obtain static pressure, subtract the velocity pressure from the total pressure
- Horizontal throw is along a surface
- Vertical throw is a free jet

PERFORMANCE DATA

TMSA / SQUARE CEILING / ROUND NECK / HIGH PERFORMANCE / HORIZONTAL TO VERTICAL DISCHARGE

| | | Neck Velocity | 400 | 500 | 600 | 700 | 800 | 1000 | 1200 | 1400 | 1600 |
|-------------|----------|---------------------|------------|-----------|---------|---------|---------|----------|----------|----------|----------|
| | | Velocity Pressure | 0.010 | 0.016 | 0.022 | 0.031 | 0.040 | 0.062 | 0.090 | 0.122 | 0.160 |
| Module Size | 6" Dia. | Airflow, cfm | 78 | 98 | 118 | 137 | 157 | 196 | 235 | 274 | 314 |
| | | Total Pressure | Horizontal | 0.018 | 0.028 | 0.040 | 0.055 | 0.072 | 0.112 | 0.162 | 0.220 |
| | | Vertical | | 0.019 | 0.030 | 0.043 | 0.058 | 0.076 | 0.118 | 0.171 | 0.232 |
| | | Throw feet | Horizontal | 2-3-5 | 2-3-6 | 3-4-7 | 3-5-8 | 3-6-8 | 4-7-9 | 4-7-10 | 4-7-11 |
| | | Vertical | | 0-1-1 | 1-1-2 | 1-1-2 | 1-1-2 | 1-1-3 | 1-1-4 | 1-2-4 | 1-2-4 |
| | 8" Dia. | NC (Noise Criteria) | Horizontal | - | - | - | 14 | 18 | 25 | 30 | 39 |
| | | Vertical | | - | - | - | 13 | 17 | 24 | 29 | 38 |
| | | Airflow, cfm | 140 | 175 | 209 | 244 | 279 | 349 | 419 | 489 | 558 |
| | | Total Pressure | Horizontal | 0.018 | 0.028 | 0.041 | 0.056 | 0.073 | 0.114 | 0.164 | 0.223 |
| | 10" Dia. | Vertical | | 0.022 | 0.034 | 0.049 | 0.067 | 0.088 | 0.137 | 0.197 | 0.269 |
| | | Throw feet | Horizontal | 2 - 3 - 5 | 2-3-6 | 3-4-8 | 3-5-9 | 3-5-10 | 4-6-11 | 5-8-12 | 6-9-13 |
| | | Vertical | | 0 - 1 - 1 | 1-1-2 | 1-1-2 | 1-1-2 | 1-1-3 | 1-2-4 | 1-2-4 | 2-2-5 |
| | | NC (Noise Criteria) | Horizontal | - | - | 12 | 17 | 21 | 28 | 33 | 38 |
| | 12" Dia. | Vertical | | - | - | 12 | 16 | 20 | 27 | 32 | 41 |
| | | Airflow, cfm | 218 | 273 | 327 | 382 | 436 | 545 | 654 | 763 | 872 |
| | | Total Pressure | Horizontal | 0.018 | 0.029 | 0.041 | 0.056 | 0.073 | 0.114 | 0.164 | 0.224 |
| | | Vertical | | 0.030 | 0.047 | 0.068 | 0.092 | 0.120 | 0.188 | 0.271 | 0.369 |
| | 14" Dia. | Throw feet | Horizontal | 2-3-6 | 3-4-8 | 3-5-10 | 4-6-11 | 4-6-13 | 5-8-14 | 6-10-15 | 8-11-17 |
| | | Vertical | | 1-1-2 | 1-1-2 | 1-1-3 | 1-2-3 | 1-2-4 | 1-2-4 | 2-3-5 | 2-3-6 |
| | | NC (Noise Criteria) | Horizontal | - | - | 15 | 20 | 24 | 31 | 37 | 41 |
| | | Vertical | | - | 12 | 18 | 22 | 26 | 33 | 38 | 45 |
| | 15" Dia. | Airflow, cfm | 428 | 535 | 641 | 748 | 855 | 1069 | 1283 | 1497 | 1710 |
| | | Total Pressure | Horizontal | 0.029 | 0.045 | 0.065 | 0.089 | 0.116 | 0.181 | 0.261 | 0.355 |
| | | Vertical | | 0.044 | 0.068 | 0.098 | 0.134 | 0.175 | 0.273 | 0.393 | 0.535 |
| | | Throw feet | Horizontal | 5-8-15 | 6-10-19 | 8-11-21 | 9-13-22 | 10-15-24 | 13-19-27 | 15-21-29 | 18-22-31 |
| | | Vertical | | 2-5-7 | 3-6-8 | 5-6-9 | 6-7-10 | 6-7-10 | 7-8-12 | 7-9-13 | 8-10-14 |
| | | NC (Noise Criteria) | Horizontal | - | - | 12 | 18 | 23 | 32 | 39 | 45 |
| | | Vertical | | 12 | 18 | 23 | 28 | 32 | 38 | 43 | 50 |

- Data obtained from tests conducted in accordance with ANSI/ASHRAE Standard 70-2006. Actual performance, with flexible duct inlet, may vary in the field. See the Engineering Guidelines section of this catalog for additional information.
- If the diffuser is mounted on an exposed duct, the throw values are 70% of those listed in the table
- Throw values given are for terminal velocities of 150, 100 and 50 fpm and for isothermal conditions. See the section, Engineering Guidelines for the catalog throw data information.
- NC values based on octave band 2 to 7 sound power levels minus a room absorption of 10 dB

- Dash (-) in space denotes an NC value of less than 10
- All pressures are given in inches of water
- Each NC value represents the noise criteria curve that will not be exceeded by the sound pressure in any of the octave bands, 2 through 7, with a room absorption of 10 dB, re 10^{-12} watts
- To obtain static pressure, subtract the velocity pressure from the total pressure
- Horizontal throw is along a surface
- Vertical throw is a free jet