



8165 E Kaiser Blvd. Anaheim, CA 92808  
www.lightlaboratory.com

Report No: L092110301P



**Report No:** L092110301P **Issue Date:** 9/8/2021

**Report Prepared For:** Horticulture Lighting Group Corp.  
3505 Maynardville Hwy, Maynardville, TN, 37807

**Model Number:** HLG 650R Diablo Update

**Test:** Photosynthetically active radiation (PAR) & Electrical measurement

**Standards Used:** Appropriate part or all test guidelines were used for test performed:  
*IESNA LM79: 2019* Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products  
*ANSI NEMA ANSLG C78.377: 2017* Specification of the Chromaticity of Solid State Lighting Products  
*ANSI C82.77-10:2014:* Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

**Description of Sample:** Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

**Special Test Condition:** Fixture is tested with no special conditions.

**Sample Arrival Date:** 9/7/21

**Date of Tests:** 9/7/21 - 9/8/21

**Seasoning of Sample:** No seasoning was performed in accordance with IESNA LM-79.

**Equipment List**

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	4/7/23
HP Power Supply	6032A	PS-DC05-S2	--
Fluke Digital Thermometer	52K/J	MT-TP05	3/17/23
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

**General Information**

<b>Manufacturer:</b>	Horticulture Lighting Group Corp.
<b>Model Number:</b>	HLG 650R Diablo Update
<b>Driver Model Number:</b>	INVENTRONICS EUD-600S560DT

**Photometric, PPF & Electrical Test Results**

<b>Total PPF (μmol/s):</b>	1780.71	* 380 - 780nm range
<b>Total PPF (μmol/s):</b>	1753.10	* 400 - 700nm range
<b>Total Radiant Flux(W):</b>	380.47	* 380 - 780nm range
<b>Total Lumens (lm):</b>	112475.70	* 380 - 780nm range
<b>PPF Efficacy (μmol/Joule):</b>	2.84	* 380 - 780nm range
<b>PPF Efficacy (μmol/Joule):</b>	2.79	* 400 - 700nm range
<b>Luminous Efficacy (lm/W):</b>	179.22	
<b>Input Voltage (VAC/60Hz):</b>	240.03	
<b>Input Current (Amp):</b>	2.6240	
<b>Input Power (W):</b>	627.60	
<b>Input Power Factor:</b>	0.9964	
<b>Current ATHD (%):</b>	5.0%	

**Test Condition**

<b>Ambient Temperature (°C):</b>	25.0
<b>Stabilization Time (Hours):</b>	0:30
<b>Total Operating Time (Hours):</b>	0:50





FIG. 1 LUMINAIRE

**Colorimetry Test Results**




**CRI & CCT**

x	0.3555
y	0.3524
u'	0.2182
v'	0.4866
CRI	85.20
CCT	4617
Duv	-0.00363

**R Values**

R1	84.70
R2	86.93
R3	87.81
R4	85.67
R5	85.23
R6	81.22
R7	88.67
R8	81.13
R9	48.78
R10	69.86
R11	85.97
R12	68.78
R13	84.53
R14	92.87
R15	84.01



## Test Methods

### Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

### Disclaimers:

The results related only to the samples as received and tested. This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government.

Report Prepared by :                     Kunjan Modi                    

Test Report Reviewed by:



Steve Kang  
Quality Assurance