







If You Ordered a Raw Brass Fixture

All raw brass will age/darken over time. If you wish to keep your fixture "like new" you can clean it periodically with Brasso. When installing the globes, **WE DO RECOMMEND WEARING GLOVES**. The raw brass will tarnish if it comes in contact with the oils on your skin.

Installation Instructions

 A photograph showing various mounting hardware components including a crossbar, a lamp nipple, a star washer, a hex nut, and two screws, all laid out on a white surface.	<p>1. Unpack your mounting hardware. The pictured items should be present along with the cap.</p>
 A close-up photograph showing a lamp nipple being secured to a crossbar with a star washer and a hex nut.	<p>2. Screw the 1in lamp nipple to the crossbar and lock it in place with the star washer and hex nut.</p>
 A photograph showing two screws used to attach a crossbar to a junction box.	<p>3. Attach the crossbar to the junction box using the provided 1" screws 4. Attach the ground wires (bare copper or green) to the ground screw. 5. Connect wires - if you do not know how to do this, please consult a certified electrician.</p>
 A photograph showing a hand sliding a light fixture onto a lamp nipple. A cap is also visible nearby.	<p>6. Slide the light fixture onto the lamp nipple as show in photo. 7. Screw on your cap to the lamp nipple to fix the light fixture to the wall.</p>